

屋内照明器具特性

品番 (品名)	S P L 5 4 2 9														
光源	LLD2000LCE1 ×4 531.0 lm														
管理番号	K0183107 (0) DB 1														
B Z 分類	B Z 5														

器具効率	77 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %			
上方光束	0 %	室指数	照明率 (X0.01)																Z C M	
下方光束	77 %																			
保守率	良 中 否	0.67	0.6	4.4	3.5	2.9	2.4	4.3	3.4	2.8	2.4	4.1	3.3	2.8	2.4	3.9	3.3	2.8	2.4	2.3
		0.63	0.8	5.2	4.3	3.7	3.3	5.1	4.2	3.7	3.2	4.9	4.1	3.6	3.2	4.7	4.0	3.6	3.2	3.0
		0.56	1.0	5.7	4.9	4.3	3.8	5.6	4.8	4.3	3.8	5.3	4.7	4.2	3.8	5.1	4.6	4.1	3.8	3.6
			1.25	6.2	5.4	4.9	4.4	6.0	5.3	4.8	4.4	5.8	5.2	4.7	4.4	5.6	5.1	4.7	4.3	4.2
下方投影面積			c m ²																	
等価発光面積			c m ²																	
取付高さ	器具間隔最大限		2.5	7.2	6.7	6.3	6.0	7.1	6.6	6.2	5.9	6.8	6.5	6.1	5.8	6.6	6.3	6.0	5.8	5.6
	横方向 (A)	縦方向 (B)	3.0	7.4	7.0	6.6	6.3	7.3	6.9	6.5	6.2	7.0	6.7	6.4	6.2	6.8	6.5	6.3	6.1	5.9
H m	1.26 H m	1.26 H m	4.0	7.6	7.3	7.0	6.7	7.5	7.2	6.9	6.7	7.3	7.0	6.8	6.6	7.1	6.9	6.7	6.5	6.3
			5.0	7.8	7.5	7.2	7.0	7.6	7.4	7.2	7.0	7.4	7.2	7.0	6.8	7.2	7.1	6.9	6.7	6.5
			7.0	7.9	7.7	7.5	7.4	7.8	7.6	7.5	7.3	7.6	7.5	7.3	7.2	7.4	7.3	7.2	7.1	6.8
			10.0	8.1	7.9	7.8	7.6	8.0	7.8	7.7	7.6	7.8	7.6	7.5	7.4	7.6	7.5	7.4	7.3	7.1

