

屋内照明器具特性

品番 (品名)	S P L 5 4 2 9	
光源	LLD3020LCE1 ×4	795.0 lm
管理番号	K0183108(0)DB1	
BZ分類	BZ1	

器具効率	80%	反射率	天井				80%				70%				50%				30%				0%
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10					
上方光束	0%																						
下方光束	80%		10%				10%				10%				10%								
		室指数	照明率 (X 0.01)																ZCM				
保守率	良	0.67	0.6	66	61	57	55	65	60	57	55	64	60	57	55	63	59	57	55	54			
	中	0.63	0.8	71	66	63	60	70	65	62	60	69	65	62	60	67	64	62	60	59			
	否	0.56	1.0	74	69	66	64	73	69	66	64	71	68	65	63	70	67	65	63	62			
下方投影面積	等価発光面積	cm ²	1.25	76	72	69	67	75	72	69	67	74	71	69	67	72	70	68	66	65			
			1.5	78	74	72	70	77	74	71	69	75	73	71	69	74	72	70	68	67			
取付高さ	器具間隔最大限		2.5	81	79	77	75	81	78	77	75	79	77	75	74	77	76	74	73	72			
	横方向 (A)	縦方向 (B)	3.0	82	80	78	77	81	80	78	76	80	78	77	76	78	77	76	75	73			
Hm	0.41Hm	0.41Hm	4.0	83	82	80	79	83	81	80	79	81	80	78	77	79	78	77	76	75			
			5.0	84	83	82	81	83	82	81	80	81	80	80	79	80	79	78	78	76			
			7.0	85	84	83	82	84	83	82	81	82	82	81	80	81	80	79	79	77			
			10.0	86	85	84	84	85	84	83	83	83	82	82	81	81	81	80	80	78			

