

屋内照明器具特性

品番 (品名)	S P L 5 4 2 9	
光源	LLD2020LCE1 ×4	460.0 l m
管理番号	K0183109 (0) DB 1	
B Z 分類	B Z 1	

器具効率	84 %	天井	80 %				70 %				50 %				30 %				0 %	
	上方光束		0 %	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
下方光束	84 %	床	10 %				10 %				10 %				10 %				0 %	
室指数	照明率 (X 0 . 0 1)																			Z C M
保守率	良	0.67	0.6	69	63	60	58	68	63	60	57	67	62	60	57	66	62	59	57	56
	中	0.63	0.8	74	69	66	63	73	68	65	63	72	68	65	63	70	67	65	63	62
	否	0.56	1.0	77	72	69	67	76	72	69	67	75	71	68	66	73	70	68	66	65
下方投影面積	等価発光面積	c m ²	1.25	79	76	73	70	79	75	72	70	77	74	72	70	76	73	71	69	68
			1.5	81	78	75	73	80	77	75	72	79	76	74	72	77	75	73	71	70
取付高さ	器具間隔最大限		2.0	83	81	78	76	83	80	78	76	81	79	77	75	79	77	76	74	73
	横方向 (A)	縦方向 (B)	2.5	85	82	80	79	84	82	80	78	82	80	79	77	81	79	78	76	75
H m	0.41 H m	0.40 H m	3.0	86	84	82	80	85	83	81	80	83	81	80	79	81	80	79	78	76
			4.0	87	85	84	82	86	84	83	82	84	83	82	81	82	81	80	80	78
			5.0	88	86	85	84	87	85	84	83	85	84	83	82	83	82	81	81	79
			7.0	88	87	86	86	87	87	86	85	86	85	84	83	84	83	83	82	80
			10.0	89	88	88	87	88	87	87	86	86	86	85	85	84	84	84	83	81

