

屋内照明器具特性	
品番 (品名)	L G B 1 5 3 0 9
光源	L L D 4 0 0 0 1 C Q 1 × 1 8 4 5 . 0 l m
管理番号	K 0 1 9 0 0 5 6 (0) D R 1
B Z 分類	B Z 4 / 0 . 7 / B Z 3

器具効率		7 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
				室指数	照明率 (X 0 . 0 1) Z C M																
保守率		良 中 否	0 . 6 7	0 . 6	4 3	3 5	3 0	2 7	4 2	3 5	3 0	2 7	4 0	3 4	3 0	2 7	3 9	3 3	2 9	2 6	2 5
			0 . 6 3	0 . 8	5 1	4 4	3 9	3 6	5 0	4 3	3 9	3 5	4 8	4 2	3 8	3 5	4 6	4 1	3 8	3 5	3 4
			0 . 5 6	1 . 0	5 5	4 9	4 5	4 1	5 4	4 9	4 5	4 1	5 3	4 8	4 4	4 1	5 1	4 7	4 3	4 1	3 9
				1 . 2 5	5 9	5 4	5 0	4 7	5 8	5 3	4 9	4 6	5 6	5 2	4 9	4 6	5 5	5 1	4 8	4 6	4 4
下方投影面積 等価発光面積		c m ² c m ²		1 . 5	6 2	5 7	5 3	5 0	6 1	5 6	5 3	5 0	5 9	5 5	5 2	4 9	5 7	5 4	5 1	4 9	4 7
				2 . 0	6 5	6 1	5 8	5 5	6 4	6 0	5 7	5 5	6 2	5 9	5 6	5 4	6 0	5 8	5 6	5 4	5 2
				2 . 5	6 7	6 4	6 1	5 8	6 6	6 3	6 0	5 8	6 4	6 2	5 9	5 7	6 2	6 0	5 8	5 7	5 5
				3 . 0	6 9	6 6	6 3	6 1	6 8	6 5	6 2	6 0	6 6	6 3	6 1	6 0	6 4	6 2	6 0	5 9	5 7
H m	1 . 3 3 H m	1 . 3 3 H m		4 . 0	7 0	6 8	6 6	6 4	6 9	6 7	6 5	6 4	6 7	6 6	6 4	6 3	6 6	6 4	6 3	6 2	6 0
				5 . 0	7 1	6 9	6 8	6 6	7 0	6 9	6 7	6 5	6 8	6 7	6 6	6 4	6 7	6 5	6 4	6 3	6 1
				7 . 0	7 2	7 1	7 0	6 8	7 1	7 0	6 9	6 8	7 0	6 9	6 8	6 7	6 8	6 7	6 6	6 5	6 3
				1 0 . 0	7 3	7 2	7 1	7 0	7 2	7 1	7 1	7 0	7 1	7 0	6 9	6 8	6 9	6 8	6 8	6 7	6 5

