

屋内照明器具特性

品番 (品名)	XLGB3309														
光源	LLD3000CU1 x1 795.0 l m														
管理番号	K0179114 (0) DR 1														
BZ分類	BZ5/1.8/BZ4/6.0/BZ5/8.5/BZ4														

器具効率	86 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束	1 %	反射率	10 %				10 %				10 %				10 %				0 %	
下方光束	85 %		床	10 %				10 %				10 %				10 %				0 %
		室指数	照明率 (X0.01)															ZCM		
保守率	良 中 否 0.67 0.63 0.56	0.6	49	38	32	27	48	38	32	27	46	37	31	27	44	36	31	27	25	
		0.8	57	48	41	36	56	47	41	36	54	46	40	36	52	45	40	36	34	
		1.0	63	54	48	43	62	53	47	43	59	52	47	42	57	51	46	42	40	
		1.25	68	60	54	49	67	59	54	49	64	58	53	49	62	56	52	48	46	
下方投影面積	c m ²	1.5	72	64	59	54	70	64	58	54	68	62	57	53	65	60	56	53	51	
		2.0	77	71	65	61	75	70	65	61	73	68	64	60	70	66	63	60	57	
取付高さ	器具間隔最大限		2.5	80	74	70	66	78	73	69	66	76	72	68	65	73	70	67	64	62
	横方向 (A)	縦方向 (B)	3.0	82	77	73	70	80	76	73	69	78	74	71	68	75	72	70	67	65
H m	1.29 H m	1.29 H m	4.0	84	81	78	75	83	80	77	74	81	78	75	73	78	76	74	72	70
			5.0	86	83	80	78	85	82	80	77	82	80	78	76	80	78	76	75	72
			7.0	88	86	84	82	87	85	83	81	84	83	81	79	82	81	79	78	76
			10.0	89	88	86	85	88	87	85	84	86	85	83	82	84	83	82	81	78

