

屋内照明器具特性	
品番 (品名)	L G B 1 0 8 5 4
光源	L L D 4 0 0 0 1 C Q 1 × 1 8 4 5 . 0 l m
管理番号	K 0 1 9 0 0 9 8 (1) D R 1
B Z 分類	B Z 3 / 0 . 7 / B Z 2 / 3 . 5 / B Z 3 / 6 . 0 / B Z 2

器具効率		63 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X 0 . 0 1) Z C M																
保守率		良 中 否	0 . 6 7	0 . 6	4 1	3 5	3 1	2 8	4 0	3 4	3 0	2 8	3 9	3 4	3 0	2 8	3 8	3 3	3 0	2 8	2 7
			0 . 6 3	0 . 8	4 7	4 2	3 8	3 5	4 7	4 1	3 7	3 5	4 5	4 0	3 7	3 5	4 4	4 0	3 7	3 4	3 3
			0 . 5 6	1 . 0	5 1	4 6	4 2	4 0	5 0	4 6	4 2	3 9	4 9	4 5	4 2	3 9	4 8	4 4	4 1	3 9	3 8
				1 . 2 5	5 4	5 0	4 6	4 4	5 4	4 9	4 6	4 4	5 2	4 8	4 6	4 3	5 1	4 8	4 5	4 3	4 2
下方投影面積 等価発光面積		c m ² c m ²		1 . 5	5 7	5 2	4 9	4 7	5 6	5 2	4 9	4 7	5 4	5 1	4 8	4 6	5 3	5 0	4 8	4 6	4 5
				2 . 0	5 9	5 6	5 3	5 1	5 8	5 5	5 3	5 1	5 7	5 4	5 2	5 0	5 5	5 3	5 1	5 0	4 8
				2 . 5	6 1	5 8	5 6	5 4	6 0	5 8	5 5	5 3	5 9	5 6	5 5	5 3	5 7	5 5	5 4	5 2	5 1
				3 . 0	6 2	6 0	5 8	5 6	6 1	5 9	5 7	5 5	6 0	5 8	5 6	5 5	5 8	5 7	5 5	5 4	5 3
H m	1 . 3 1 H m	1 . 3 1 H m		4 . 0	6 4	6 2	6 0	5 9	6 3	6 1	5 9	5 8	6 1	6 0	5 8	5 7	6 0	5 9	5 7	5 6	5 5
				5 . 0	6 4	6 3	6 1	6 0	6 4	6 2	6 1	6 0	6 2	6 1	6 0	5 9	6 1	6 0	5 9	5 8	5 6
				7 . 0	6 5	6 4	6 3	6 2	6 5	6 4	6 3	6 2	6 3	6 2	6 1	6 1	6 2	6 1	6 0	6 0	5 8
				1 0 . 0	6 6	6 5	6 5	6 4	6 5	6 5	6 4	6 3	6 4	6 3	6 3	6 2	6 2	6 2	6 1	6 1	5 9

