

屋内照明器具特性	
品番 (品名)	LGB10855
光源	LLD3020LCT1 ×1 795.0 lm
管理番号	K0190110 (2) DR1
BZ分類	BZ1

器具効率		89 %	反 射 率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
上方光束		0 %	室指数	照明率 (X0.01)																		Z C M
下方光束		89 %																				
保守率		良	0.67	0.6	76	71	67	65	75	70	67	65	74	70	67	65	73	69	67	65	64	
		中	0.63	0.8	81	76	73	71	80	76	73	71	79	75	73	71	78	75	72	71	70	
		否	0.56	1.0	84	80	77	75	83	79	77	75	82	79	76	74	80	78	76	74	73	
		0.56	1.25	86	83	80	78	86	82	80	78	84	81	79	78	83	80	79	77	76		
下方投影面積		c m ²		1.5	88	85	83	81	87	84	82	80	86	83	81	80	84	82	81	79	78	
等価発光面積		c m ²		2.0	90	88	86	84	89	87	85	84	88	86	84	83	86	84	83	82	81	
取付 高さ	器具間隔最大限			2.5	91	89	88	86	90	89	87	86	89	87	86	85	87	86	85	84	82	
	横方向 (A)		縦方向 (B)	3.0	92	90	89	88	91	90	88	87	89	88	87	86	88	87	86	85	83	
H m	0.42 H m		0.42 H m	4.0	93	92	91	90	92	91	90	89	90	89	88	88	89	88	87	86	85	
				5.0	94	93	92	91	93	92	91	90	91	90	89	89	89	89	88	87	85	
				7.0	94	94	93	92	93	93	92	91	92	91	90	90	90	89	89	89	86	
				10.0	95	94	94	93	94	93	93	93	92	92	91	91	90	90	90	89	87	

