

屋内照明器具特性	
品番 (品名)	L G B 1 6 1 5 5
光源	LLD4000LCE1 ×1 845.0 l m
管理番号	K0190088 (1) DR 1
B Z 分類	BZ3 / 0.7 / BZ2 / 1.8 / BZ3

器具効率		65 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) Z C M																
保守率		良 中 否	0.67	0.6	42	36	31	28	42	35	31	28	40	35	31	28	39	34	31	28	27
			0.63	0.8	49	43	39	36	48	42	39	36	46	42	38	35	45	41	38	35	34
			0.56	1.0	53	47	44	41	52	47	43	41	50	46	43	40	49	45	42	40	39
				1.25	56	51	48	45	55	51	48	45	54	50	47	44	52	49	46	44	43
下方投影面積		c m ²		1.5	58	54	51	48	58	54	50	48	56	52	50	47	54	51	49	47	46
			等価発光面積	c m ²	2.0	61	58	55	52	60	57	54	52	59	56	54	52	57	55	53	51
取付 高さ	器具間隔最大限			2.5	63	60	58	55	62	59	57	55	60	58	56	54	59	57	55	54	52
	横方向 (A) 縦方向 (B)			3.0	64	62	59	57	63	61	59	57	62	60	58	56	60	58	57	56	54
H m	1.32 H m	1.32 H m		4.0	66	64	62	60	65	63	61	60	63	62	60	59	62	60	59	58	56
				5.0	67	65	63	62	66	64	63	62	64	63	62	61	63	61	60	60	58
				7.0	68	66	65	64	67	66	65	64	65	64	63	62	64	63	62	61	60
				10.0	68	68	67	66	68	67	66	65	66	65	65	64	64	64	63	63	61

