

屋内照明器具特性	
品番 (品名)	L G B 1 6 1 5 5
光源	LLD20001CQ1 ×1 531.0 lm
管理番号	K0190099 (1) DR 1
B Z 分類	BZ3 / 0.9 / BZ2 / 1.4 / BZ3

器具効率		67 %	反射率	天井	80 %				70 %				50 %				30 %				0 %			
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
				床	10 %				10 %				10 %				10 %				0 %			
上方光束		1 %	室指数	照明率 (X0.01)																			Z	CM
下方光束		66 %																						
保守率		良 中 否	0.67	0.6	44	37	32	29	43	36	32	29	41	36	32	29	40	35	31	29	28			
			0.63	0.8	50	44	40	37	49	44	40	37	48	43	39	36	46	42	39	36	35			
			0.56	1.0	54	49	45	42	53	48	44	42	52	47	44	41	50	46	43	41	40			
				1.25	58	53	49	46	57	52	49	46	55	51	48	46	53	50	47	45	44			
下方投影面積		cm ²	1.5	60	56	52	49	59	55	52	49	57	54	51	49	56	53	50	48	47				
等価発光面積		cm ²	2.0	63	59	56	54	62	59	56	54	60	57	55	53	59	56	54	52	51				
取付 高さ	器具間隔最大限		2.5	65	62	59	57	64	61	59	56	62	60	58	56	60	58	57	55	53				
	横方向 (A)		縦方向 (B)	3.0	66	63	61	59	65	63	60	59	63	61	59	58	62	60	58	57	55			
H m	1.31 H m	1.31 H m	4.0	68	65	64	62	67	65	63	61	65	63	62	60	63	62	61	59	58				
			5.0	68	67	65	64	68	66	65	63	66	64	63	62	64	63	62	61	59				
			7.0	70	68	67	66	69	67	66	65	67	66	65	64	65	64	64	63	61				
			10.0	70	69	69	68	69	69	68	67	68	67	66	66	66	66	65	64	63				

