

屋内照明器具特性

品番 (品名)	NNN61511WZ	
光源	LDA7L-H/S/6 ×1	810.0 lm
管理番号	K0178345(0)DB1	
BZ分類	BZ3	

器具効率	58%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	0%	床	10%				10%				10%				10%				0%	
下方光束	58%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.67	0.6	3.8	3.2	2.8	2.5	3.7	3.1	2.8	2.5	3.6	3.1	2.8	2.5	3.5	3.0	2.7	2.5	2.4
	中	0.63	0.8	4.3	3.8	3.4	3.1	4.2	3.7	3.4	3.1	4.1	3.7	3.4	3.1	4.0	3.6	3.3	3.1	3.0
	否	0.56	1.0	4.7	4.2	3.8	3.6	4.6	4.1	3.8	3.5	4.5	4.1	3.8	3.5	4.3	4.0	3.7	3.5	3.4
			1.25	5.0	4.5	4.2	3.9	4.9	4.5	4.2	3.9	4.7	4.4	4.1	3.9	4.6	4.3	4.1	3.9	3.8
下方投影面積		cm ²	1.5	5.2	4.8	4.5	4.2	5.1	4.7	4.4	4.2	4.9	4.6	4.4	4.2	4.8	4.5	4.3	4.1	4.0
等価発光面積		cm ²	2.0	5.4	5.1	4.8	4.6	5.4	5.1	4.8	4.6	5.2	4.9	4.7	4.6	5.1	4.8	4.7	4.5	4.4
取付高さ	器具間隔最大限		2.5	5.6	5.3	5.1	4.9	5.5	5.3	5.0	4.9	5.4	5.2	5.0	4.8	5.2	5.0	4.9	4.8	4.6
	横方向 (A)	縦方向 (B)	3.0	5.7	5.5	5.3	5.1	5.6	5.4	5.2	5.1	5.5	5.3	5.1	5.0	5.3	5.2	5.0	4.9	4.8
Hm	1.10Hm	1.10Hm	4.0	5.8	5.7	5.5	5.3	5.8	5.6	5.4	5.3	5.6	5.5	5.3	5.2	5.5	5.4	5.3	5.2	5.0
			5.0	5.9	5.8	5.6	5.5	5.8	5.7	5.6	5.5	5.7	5.6	5.5	5.4	5.6	5.5	5.4	5.3	5.1
			7.0	6.0	5.9	5.8	5.7	5.9	5.8	5.7	5.7	5.8	5.7	5.6	5.6	5.7	5.6	5.5	5.5	5.3
			10.0	6.1	6.0	5.9	5.9	6.0	5.9	5.9	5.8	5.9	5.8	5.8	5.7	5.7	5.7	5.6	5.6	5.4

