

|          |                              |
|----------|------------------------------|
| 屋内照明器具特性 |                              |
| 品番 (品名)  | LGB50642                     |
| 光源       | LED5000_70_3620 x1 3620.0 lm |
| 管理番号     | K0178697(0)DB1               |
| BZ分類     | BZ6                          |

|        |         |                 |               |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |  |  |     |
|--------|---------|-----------------|---------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|--|--|-----|
| 器具効率   | 100%    | 天井              | 80%           |     |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |     |     | 0%  |     |  |  |     |
|        |         | 壁               | 70            | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 0%  |     |  |  |     |
| 上方光束   | 15%     | 床               | 10%           |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 0%  |     |  |  |     |
| 下方光束   | 85%     | 室指数             | 照明率 ( X0.01 ) |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |  |  | ZCM |
| 保守率    | 良       | 0.69            | 0.6           | 5.2 | 3.9 | 3.1 | 2.5 | 5.0 | 3.8 | 3.0 | 2.5 | 4.6 | 3.6 | 2.9 | 2.4 | 4.2 | 3.3 | 2.7 | 2.3 | 2.0 |  |  |     |
|        | 中       | 0.67            | 0.8           | 6.1 | 4.9 | 4.0 | 3.4 | 5.9 | 4.7 | 3.9 | 3.4 | 5.4 | 4.4 | 3.8 | 3.2 | 5.0 | 4.2 | 3.6 | 3.1 | 2.8 |  |  |     |
|        | 否       | 0.63            | 1.0           | 6.7 | 5.6 | 4.7 | 4.1 | 6.5 | 5.4 | 4.6 | 4.0 | 6.0 | 5.1 | 4.4 | 3.9 | 5.5 | 4.7 | 4.2 | 3.7 | 3.3 |  |  |     |
|        |         |                 | 1.25          | 7.3 | 6.2 | 5.4 | 4.8 | 7.0 | 6.0 | 5.3 | 4.7 | 6.5 | 5.7 | 5.0 | 4.5 | 6.0 | 5.3 | 4.8 | 4.3 | 3.9 |  |  |     |
| 下方投影面積 |         | cm <sup>2</sup> | 1.5           | 7.7 | 6.7 | 6.0 | 5.3 | 7.4 | 6.5 | 5.8 | 5.2 | 6.9 | 6.1 | 5.5 | 5.0 | 6.4 | 5.7 | 5.2 | 4.8 | 4.3 |  |  |     |
| 等価発光面積 |         | cm <sup>2</sup> | 2.0           | 8.3 | 7.4 | 6.7 | 6.1 | 8.0 | 7.2 | 6.6 | 6.0 | 7.4 | 6.8 | 6.2 | 5.7 | 6.9 | 6.3 | 5.9 | 5.5 | 5.0 |  |  |     |
| 取付高さ   | 器具間隔最大限 |                 | 2.5           | 8.7 | 7.9 | 7.3 | 6.7 | 8.3 | 7.7 | 7.1 | 6.6 | 7.8 | 7.2 | 6.7 | 6.3 | 7.2 | 6.7 | 6.3 | 6.0 | 5.4 |  |  |     |
|        | 横方向 (A) | 縦方向 (B)         | 3.0           | 8.9 | 8.2 | 7.7 | 7.2 | 8.6 | 8.0 | 7.5 | 7.0 | 8.0 | 7.5 | 7.1 | 6.7 | 7.5 | 7.1 | 6.7 | 6.4 | 5.8 |  |  |     |
| 1.5m   | 2.1m    | 2.28m           | 4.0           | 9.3 | 8.7 | 8.2 | 7.8 | 8.9 | 8.4 | 8.0 | 7.6 | 8.4 | 7.9 | 7.6 | 7.2 | 7.8 | 7.5 | 7.2 | 6.9 | 6.3 |  |  |     |
| 2      | 2.76    | 2.81            | 5.0           | 9.5 | 9.0 | 8.6 | 8.2 | 9.2 | 8.7 | 8.3 | 8.0 | 8.6 | 8.2 | 7.9 | 7.6 | 8.0 | 7.7 | 7.5 | 7.2 | 6.6 |  |  |     |
| 2.5    | 3.43    | 3.39            | 7.0           | 9.7 | 9.4 | 9.0 | 8.7 | 9.4 | 9.1 | 8.8 | 8.5 | 8.9 | 8.6 | 8.3 | 8.1 | 8.3 | 8.1 | 7.9 | 7.7 | 7.0 |  |  |     |
| 3      | 4.1     | 3.97            | 10.0          | 9.9 | 9.7 | 9.4 | 9.2 | 9.6 | 9.4 | 9.1 | 8.9 | 9.1 | 8.9 | 8.7 | 8.5 | 8.5 | 8.4 | 8.2 | 8.0 | 7.4 |  |  |     |

