

屋内照明器具特性

品番 (品名)	XLGB1721									
光源	LLD3000CU1 x1					795.0 lm				
管理番号	K0178766(0)DR1									
BZ分類	BZ1/1.1/BZ2									

器具効率	60%	天井	80%				70%				50%				30%				0%	
	上方光束 1%		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				下方光束 59%	10%				10%				10%				10%			
室指数	照明率 (X0.01)																			ZCM
保守率	良	0.67	0.6	43	38	34	32	42	37	34	32	41	37	34	32	40	36	33	32	31
	中	0.63	0.8	48	43	40	37	47	43	40	37	46	42	39	37	45	41	39	37	36
	否	0.56	1.0	51	47	44	41	50	46	43	41	49	45	43	41	47	45	42	40	39
			1.25	54	50	47	45	53	49	47	45	51	48	46	44	50	47	45	44	42
下方投影面積			1.5	56	52	49	47	55	51	49	47	53	50	48	46	52	49	47	46	45
			2.0	58	55	53	51	57	54	52	50	55	53	51	50	54	52	50	49	48
取付高さ	器具間隔最大限		2.5	59	57	55	53	58	56	54	53	57	55	53	52	55	54	52	51	50
	横方向 (A)	縦方向 (B)	3.0	60	58	56	55	59	57	56	54	58	56	55	53	56	55	54	53	51
Hm	1.26Hm	1.26Hm	4.0	61	60	58	57	61	59	58	57	59	58	56	55	57	56	55	54	53
			5.0	62	61	60	58	61	60	59	58	60	59	58	57	58	57	56	56	54
			7.0	63	62	61	60	62	61	60	60	60	60	59	58	59	58	58	57	55
			10.0	64	63	62	62	63	62	61	61	61	60	60	59	59	59	59	58	56

