

屋内照明器具特性	
品番(品名)	LGB81642Z
光源	LDA7L-H/S/6 x1 810.0lm
管理番号	K0179177(0)DB1
BZ分類	BZ5

器具効率	94%	反射率	天井	80%				70%				50%				30%				0%			
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%			
			床	10%				10%				10%				10%				0%			
上方光束	23%	室指数	照明率 (x0.01)																				ZCM
下方光束	71%																						
保守率	良 中 否	0.67	0.6	51	40	32	28	48	38	31	27	44	35	30	25	40	33	28	24	21			
		0.63	0.8	59	49	41	36	56	47	40	35	51	43	38	33	47	40	35	32	28			
		0.56	1.0	65	55	48	43	62	53	46	41	56	49	43	39	51	45	41	37	32			
			1.25	70	61	54	49	67	59	53	48	61	54	49	45	55	50	46	42	37			
下方投影面積	c m ²	1.5	74	66	59	54	71	63	57	52	64	58	53	49	58	53	49	46	40				
		2.0	79	72	66	61	75	69	64	59	69	64	59	55	63	58	55	52	45				
取付高さ	器具間隔最大限		2.5	82	76	71	66	78	73	68	64	72	67	63	60	65	62	59	56	49			
	横方向(A)	縦方向(B)	3.0	84	79	74	70	81	76	71	68	74	70	66	63	67	64	61	59	52			
Hm	1.22Hm	1.31Hm	4.0	87	83	79	75	83	79	76	73	76	73	70	68	70	67	65	63	55			
			5.0	89	85	82	79	85	82	79	76	78	75	73	71	72	69	67	66	58			
			7.0	91	88	85	83	87	85	82	80	80	78	76	74	74	72	70	69	61			
			10.0	93	90	88	86	89	87	85	83	82	80	79	77	75	74	73	72	63			

