

屋内照明器具特性	
品番 (品名)	L G B 1 6 1 5 9
光源	L L D 4 0 0 0 M L C E 1 × 1 8 4 5 . 0 l m
管理番号	K 0 1 9 0 0 9 2 (1) D R 1
B Z 分類	B Z 3 / 0 . 9 / B Z 2 / 1 . 8 / B Z 3

器具効率		6 4 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束		1 %	室指数	照明率 (X 0 . 0 1)																			Z C M
下方光束		6 3 %																					
保守率		良 中 否	0 . 6 7	0 . 6	4 2	3 5	3 1	2 8	4 1	3 5	3 1	2 8	3 9	3 4	3 0	2 8	3 8	3 3	3 0	2 8	2 6		
			0 . 6 3	0 . 8	4 8	4 2	3 8	3 5	4 7	4 2	3 8	3 5	4 6	4 1	3 7	3 5	4 4	4 0	3 7	3 5	3 3		
			0 . 5 6	1 . 0	5 2	4 7	4 3	4 0	5 1	4 6	4 2	4 0	4 9	4 5	4 2	3 9	4 8	4 4	4 1	3 9	3 8		
				1 . 2 5	5 5	5 0	4 7	4 4	5 4	5 0	4 7	4 4	5 3	4 9	4 6	4 4	5 1	4 8	4 5	4 3	4 2		
下方投影面積		c m ²	1 . 5	5 7	5 3	5 0	4 7	5 6	5 3	4 9	4 7	5 5	5 1	4 9	4 6	5 3	5 0	4 8	4 6	4 5			
等価発光面積		c m ²	2 . 0	6 0	5 7	5 4	5 1	5 9	5 6	5 3	5 1	5 8	5 5	5 3	5 1	5 6	5 4	5 2	5 0	4 9			
取付 高さ	器具間隔最大限		2 . 5	6 2	5 9	5 6	5 4	6 1	5 8	5 6	5 4	5 9	5 7	5 5	5 3	5 8	5 6	5 4	5 3	5 1			
	横方向 (A) 縦方向 (B)		3 . 0	6 3	6 1	5 8	5 6	6 2	6 0	5 8	5 6	6 0	5 9	5 7	5 5	5 9	5 7	5 6	5 4	5 3			
H m	1 . 3 2 H m	1 . 3 2 H m	4 . 0	6 5	6 3	6 1	5 9	6 4	6 2	6 0	5 9	6 2	6 0	5 9	5 8	6 0	5 9	5 8	5 7	5 5			
			5 . 0	6 5	6 4	6 2	6 1	6 5	6 3	6 2	6 0	6 3	6 2	6 0	5 9	6 1	6 0	5 9	5 8	5 7			
			7 . 0	6 6	6 5	6 4	6 3	6 6	6 4	6 3	6 2	6 4	6 3	6 2	6 1	6 2	6 2	6 1	6 0	5 8			
			1 0 . 0	6 7	6 6	6 5	6 5	6 6	6 6	6 5	6 4	6 5	6 4	6 3	6 3	6 3	6 3	6 2	6 2	6 0			

