

屋内照明器具特性	
品番 (品名)	LGB16159
光源	LLD5010LCC1 ×1 1095.0 l m
管理番号	K0190107 (1) DR 1
BZ分類	BZ1

器具効率		93 %	反 射 率	天井	80 %				70 %				50 %				30 %				0 %						
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %						
				床	10 %				10 %				10 %				10 %				0 %						
上方光束		0 %	室指数	照明率 (X0.01)																				Z C M			
下方光束		93 %																									
保守率		良 中 否	0.67	0.6	80	75	71	69	79	74	71	69	78	74	71	69	77	73	71	69	68						
			0.63	0.8	85	80	77	75	84	80	77	75	83	79	76	74	82	78	76	74	73						
			0.56	1.0	88	84	81	79	87	84	81	79	86	83	80	78	85	82	80	78	77						
			1.25	91	87	84	82	90	87	84	82	88	85	83	81	87	84	83	81	80							
下方投影面積		c m ²	1.5	92	89	87	85	92	89	86	84	90	87	85	84	88	86	85	83	82							
			2.0	95	92	90	88	94	91	89	88	92	90	88	87	90	89	87	86	84							
等価発光面積		c m ²	2.5	96	94	92	90	95	93	91	90	93	91	90	89	91	90	89	88	86							
			3.0	97	95	93	92	96	94	92	91	94	92	91	90	92	91	90	89	87							
H m	0.82 H m	0.82 H m	4.0	98	96	95	94	97	95	94	93	95	94	93	92	93	92	91	91	89							
			5.0	98	97	96	95	97	96	95	94	95	95	94	93	94	93	92	92	89							
			7.0	99	98	97	97	98	97	97	96	96	95	95	94	94	94	93	93	90							
			10.0	100	99	98	98	99	98	98	97	97	96	96	95	95	94	94	94	91							

