

屋内照明器具特性

品番 (品名)	NNN61511WZ															
光源	LDA7L-G/K6 x1				810.0lm											
管理番号	K0178347(0)DB1															
BZ分類	BZ3															

器具効率	55%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	0%	室指数	照明率 (X0.01)																ZCM		
下方光束	55%																				
保守率	良 中 否	0.67	0.6	3.5	3.0	2.6	2.3	3.5	2.9	2.6	2.3	3.4	2.9	2.5	2.3	3.3	2.8	2.5	2.3	2.2	
		0.63	0.8	4.1	3.6	3.2	2.9	4.0	3.5	3.2	2.9	3.9	3.4	3.1	2.9	3.8	3.4	3.1	2.9	2.8	
		0.56	1.0	4.4	3.9	3.6	3.3	4.4	3.9	3.6	3.3	4.2	3.8	3.5	3.3	4.1	3.8	3.5	3.3	3.2	
			1.25	4.7	4.3	4.0	3.7	4.7	4.3	3.9	3.7	4.5	4.2	3.9	3.7	4.4	4.1	3.8	3.7	3.5	
下方投影面積	c m ²	1.5	4.9	4.5	4.2	4.0	4.8	4.5	4.2	4.0	4.7	4.4	4.1	3.9	4.6	4.3	4.1	3.9	3.8		
		2.0	5.2	4.9	4.6	4.4	5.1	4.8	4.6	4.4	5.0	4.7	4.5	4.3	4.8	4.6	4.4	4.3	4.2		
取付高さ	器具間隔最大限		2.5	5.3	5.1	4.8	4.7	5.3	5.0	4.8	4.6	5.1	4.9	4.7	4.6	5.0	4.8	4.7	4.5	4.4	
	横方向 (A)	縦方向 (B)	3.0	5.5	5.2	5.0	4.8	5.4	5.2	5.0	4.8	5.2	5.1	4.9	4.7	5.1	4.9	4.8	4.7	4.6	
H m	1.15 H m	1.15 H m	4.0	5.6	5.4	5.2	5.1	5.5	5.3	5.2	5.1	5.4	5.2	5.1	5.0	5.2	5.1	5.0	4.9	4.8	
			5.0	5.7	5.5	5.4	5.3	5.6	5.5	5.3	5.2	5.5	5.3	5.2	5.1	5.3	5.2	5.1	5.1	4.9	
			7.0	5.8	5.6	5.5	5.5	5.7	5.6	5.5	5.4	5.6	5.5	5.4	5.3	5.4	5.4	5.3	5.2	5.1	
			10.0	5.8	5.8	5.7	5.6	5.8	5.7	5.6	5.6	5.6	5.6	5.5	5.5	5.5	5.5	5.4	5.4	5.2	

