

屋内照明器具特性

品番 (品名)	XLGB1405				
光源	LLD3000CU1	x1	795.0	lm	
管理番号	K0179027(0)DR1				
BZ分類	BZ5				

器具効率	78%	天井	80%				70%				50%				30%				0%		
	上方光束		4%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		74%		床	10%				10%				10%				10%			
室指数	照明率 (X0.01)																			ZCM	
保守率	良	0.67	0.6	4.2	3.2	2.6	2.2	4.1	3.2	2.6	2.1	3.9	3.0	2.5	2.1	3.6	2.9	2.4	2.1	1.9	
	中	0.63	0.8	5.0	4.0	3.4	2.9	4.8	4.0	3.3	2.9	4.6	3.8	3.3	2.9	4.3	3.7	3.2	2.8	2.6	
	否	0.56	1.0	5.5	4.6	4.0	3.5	5.3	4.5	3.9	3.4	5.0	4.3	3.8	3.4	4.8	4.2	3.7	3.3	3.1	
			1.25	5.9	5.1	4.5	4.0	5.8	5.0	4.5	4.0	5.5	4.8	4.3	3.9	5.2	4.6	4.2	3.9	3.6	
下方投影面積			c m ²	1.5	6.3	5.5	4.9	4.5	6.1	5.4	4.9	4.4	5.8	5.2	4.7	4.3	5.5	5.0	4.6	4.2	4.0
	等価発光面積		c m ²	2.0	6.7	6.1	5.6	5.1	6.5	6.0	5.5	5.1	6.2	5.7	5.3	5.0	5.9	5.5	5.2	4.8	4.6
取付高さ	器具間隔最大限			2.5	7.0	6.4	6.0	5.6	6.8	6.3	5.9	5.5	6.5	6.1	5.7	5.4	6.2	5.8	5.5	5.3	5.0
	横方向 (A)	縦方向 (B)		3.0	7.2	6.7	6.3	5.9	7.0	6.6	6.2	5.9	6.7	6.3	6.0	5.7	6.4	6.1	5.8	5.6	5.3
H m	1.18 H m	1.18 H m		4.0	7.5	7.1	6.7	6.4	7.3	6.9	6.6	6.3	7.0	6.7	6.4	6.2	6.7	6.4	6.2	6.0	5.7
				5.0	7.6	7.3	7.0	6.7	7.5	7.2	6.9	6.6	7.1	6.9	6.7	6.4	6.9	6.6	6.4	6.3	5.9
				7.0	7.8	7.6	7.3	7.1	7.6	7.4	7.2	7.0	7.3	7.2	7.0	6.8	7.1	6.9	6.8	6.6	6.3
				10.0	8.0	7.8	7.6	7.4	7.8	7.6	7.5	7.3	7.5	7.4	7.2	7.1	7.2	7.1	7.0	6.9	6.6

