

# 屋内照明器具特性

品番 (品名)	LGD9101K				
光源	LLD3000CU1 x1 795.0 lm				
管理番号	K0178936(0)DR1				
BZ分類	BZ4/0.7/BZ3				

器具効率	68%	天井	80%				70%				50%				30%				0%																																							
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%																																							
		床	10%				10%				10%				10%				0%																																							
上方光束	0%	室指数																			照明率 (X0.01)																			ZCM																		
下方光束	68%																																																									
保守率	良 中 否	0.67	0.6	4.2	3.4	2.9	2.6	4.1	3.4	2.9	2.6	3.9	3.3	2.9	2.6	3.8	3.2	2.9	2.6	2.4																																						
		0.63	0.8	4.9	4.2	3.7	3.4	4.8	4.2	3.7	3.4	4.6	4.1	3.7	3.4	4.5	4.0	3.6	3.3	3.2																																						
		0.56	1.0	5.3	4.7	4.3	3.9	5.3	4.7	4.3	3.9	5.1	4.6	4.2	3.9	4.9	4.5	4.2	3.9	3.8																																						
			1.25	5.7	5.2	4.8	4.5	5.6	5.1	4.8	4.5	5.5	5.0	4.7	4.4	5.3	4.9	4.6	4.4	4.3																																						
下方投影面積	c m <sup>2</sup>	1.5	6.0	5.5	5.1	4.8	5.9	5.5	5.1	4.8	5.7	5.3	5.0	4.8	5.6	5.2	5.0	4.7	4.6																																							
		2.0	6.4	6.0	5.6	5.4	6.3	5.9	5.6	5.3	6.1	5.8	5.5	5.3	5.9	5.7	5.4	5.2	5.1																																							
取付高さ	器具間隔最大限		2.5	6.6	6.2	6.0	5.7	6.5	6.2	5.9	5.7	6.3	6.0	5.8	5.6	6.1	5.9	5.7	5.6	5.4																																						
	横方向 (A)	縦方向 (B)	3.0	6.7	6.4	6.2	6.0	6.6	6.3	6.1	5.9	6.4	6.2	6.0	5.8	6.3	6.1	5.9	5.8	5.6																																						
H m	1.23 H m	1.23 H m	4.0	6.9	6.6	6.4	6.3	6.8	6.6	6.4	6.2	6.6	6.4	6.3	6.1	6.4	6.3	6.2	6.1	5.9																																						
			5.0	7.0	6.8	6.6	6.5	6.9	6.7	6.6	6.4	6.7	6.6	6.4	6.3	6.5	6.4	6.3	6.2	6.1	6.1																																					
			7.0	7.1	6.9	6.8	6.7	7.0	6.9	6.8	6.7	6.8	6.7	6.6	6.5	6.7	6.6	6.5	6.4	6.2																																						
			10.0	7.2	7.1	7.0	6.9	7.1	7.0	6.9	6.8	6.9	6.8	6.8	6.7	6.8	6.7	6.6	6.6	6.4																																						

