

屋内照明器具特性	
品番 (品名)	LGD9101K
光源	LLD2000LCT1 ×1      531.0 lm
管理番号	K0189131 (1) DR1
BZ分類	BZ3/1.1/BZ2

器具効率	64%	反射率	天井	80%				70%				50%				30%				0%		
	上方光束		0%	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
	下方光束		64%	床	10%				10%				10%				10%				0%	
	室指数		照明率 (×0.01)																			
保守率	良	0.67	0.6	40	34	29	26	40	33	29	26	38	33	29	26	37	32	28	26	25		
	中	0.63	0.8	47	41	37	34	47	41	37	34	45	40	36	34	44	39	36	34	32		
	否	0.56	1.0	52	46	42	39	51	46	42	39	49	45	42	39	48	44	41	39	38		
			1.25	55	51	47	44	55	50	47	44	53	49	46	44	51	48	46	44	42		
下方投影面積	cm <sup>2</sup>		1.5	58	54	50	48	57	53	50	47	55	52	49	47	54	51	49	47	45		
	等価発光面積		cm <sup>2</sup>	2.0	61	57	55	52	60	57	54	52	58	56	53	52	57	55	53	51	50	
取付高さ	器具間隔最大限		2.5	62	60	57	55	62	59	57	55	60	58	56	54	59	57	55	54	52		
	横方向 (A)	縦方向 (B)	3.0	64	61	59	57	63	61	59	57	61	59	58	56	60	58	57	56	54		
Hm	1.22Hm	1.22Hm	4.0	65	63	62	60	64	63	61	60	63	61	60	59	61	60	59	58	56		
			5.0	66	64	63	62	65	64	62	61	64	62	61	60	62	61	60	59	58		
			7.0	67	66	65	64	66	65	64	63	65	64	63	62	63	62	62	61	59		
			10.0	68	67	66	65	67	66	65	65	65	65	64	64	64	63	63	62	61		

