

# 屋内照明器具特性

品番 (品名)	LGD9102K	
光源	LLD5010LCC1 ×1	1095.0 1m
管理番号	K0188662(0)DR1	
BZ分類	BZ1	

器具効率	99%	天井	80%				70%				50%				30%				0%	
	上方光束 1%		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	98%	床		10%				10%				10%				10%				0%
室指数	照明率 (X0.01)																			ZCM
保守率	良	0.67	0.6	83	78	74	71	83	77	74	71	81	76	73	71	80	76	73	71	70
	中	0.63	0.8	89	83	80	77	88	83	79	77	86	82	79	77	85	81	78	76	75
	否	0.56	1.0	92	87	84	81	91	87	83	81	89	86	83	81	88	85	82	80	79
下方投影面積	等価発光面積	cm <sup>2</sup>	1.25	95	91	87	85	94	90	87	85	92	89	86	84	90	88	85	83	82
			1.5	97	93	90	88	96	92	89	87	94	91	88	86	92	90	87	86	84
取付高さ	器具間隔最大限		2.5	101	98	96	94	100	97	95	93	98	96	94	92	96	94	92	91	89
	横方向 (A)	縦方向 (B)	3.0	102	100	98	96	101	99	97	95	99	97	95	94	97	95	94	93	90
Hm	0.81Hm	0.81Hm	4.0	103	101	100	98	102	100	99	97	100	98	97	96	98	97	95	95	92
			5.0	104	102	101	100	103	101	100	99	101	99	98	97	98	97	97	96	93
			7.0	105	104	103	102	104	103	102	101	101	100	99	99	98	98	97	95	
			10.0	106	105	104	103	104	104	103	102	102	101	101	100	100	99	99	98	95

