

# 屋内照明器具特性

品番 (品名)	LGD9102K	
光源	LLD5020LCC1 ×1	1085.0 lm
管理番号	K0188664(0)DR1	
BZ分類	BZ1	

器具効率	99%	天井	80%				70%				50%				30%				0%	
	上方光束 1%		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	98%	床		10%				10%				10%				10%				0%
室指数	照明率 (X0.01)																			ZCM
保守率	良 0.67	0.6	78	70	66	63	77	70	66	63	75	69	65	62	74	68	65	62	61	
	中 0.63	0.8	84	78	73	70	83	77	73	70	81	76	72	69	80	75	72	69	68	
	否 0.56	1.0	88	82	78	75	87	82	78	75	85	81	77	74	83	79	76	74	72	
下方投影面積 等価発光面積	cm <sup>2</sup>	1.25	92	87	83	80	91	86	82	79	89	84	81	79	87	83	80	78	76	
		1.5	94	90	86	83	93	89	85	83	91	87	84	82	89	86	83	81	79	
取付高さ	器具間隔最大限		2.5	99	96	93	91	98	95	93	90	96	93	91	89	94	91	90	88	86
	横方向 (A)	縦方向 (B)	3.0	101	98	95	93	99	97	94	93	97	95	93	91	95	93	91	90	88
Hm	0.42Hm	0.42Hm	4.0	102	100	98	96	101	99	97	95	99	97	95	94	96	95	94	92	90
			5.0	103	101	100	98	102	100	99	97	99	98	97	96	97	96	95	94	91
			7.0	104	103	102	100	103	102	101	99	101	100	99	98	98	97	97	96	93
			10.0	105	104	103	102	104	103	102	101	101	101	100	99	99	98	98	97	94

