

屋内照明器具特性

品番 (品名)	NTN88081B				
光源	LLD2000MLCE1 ×1 531.0 l m				
管理番号	K0179224 (0) DR 1				
BZ分類	BZ5				

器具効率	98 %	天井	80 %				70 %				50 %				30 %				0 %																																	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %																																	
		床	10 %				10 %				10 %				10 %				0 %																																	
上方光束	6 %	室指数																	照明率 (X0.01)																	ZCM																
下方光束	92 %																																																			
保守率	良 中 否	0.69	0.6	5.4	4.2	3.5	2.9	5.3	4.1	3.4	2.9	5.0	4.0	3.3	2.9	4.7	3.9	3.3	2.8	2.6																																
		0.67	0.8	6.4	5.2	4.5	3.9	6.2	5.1	4.4	3.9	5.9	5.0	4.3	3.8	5.6	4.8	4.2	3.7	3.5																																
			1.0	7.0	6.0	5.2	4.6	6.8	5.8	5.1	4.6	6.5	5.6	5.0	4.5	6.1	5.4	4.9	4.4	4.1																																
		0.63	1.25	7.6	6.6	5.9	5.3	7.4	6.5	5.8	5.3	7.0	6.3	5.7	5.2	6.7	6.0	5.5	5.1	4.8																																
下方投影面積	c m ²	1.5	8.0	7.1	6.4	5.9	7.8	7.0	6.3	5.8	7.4	6.7	6.2	5.7	7.1	6.5	6.0	5.6	5.3																																	
		2.0	8.6	7.8	7.2	6.7	8.4	7.7	7.1	6.6	8.0	7.4	6.9	6.5	7.6	7.1	6.7	6.3	6.0																																	
取付高さ	器具間隔最大限		2.5	8.9	8.3	7.7	7.3	8.7	8.1	7.6	7.2	8.3	7.8	7.4	7.0	7.9	7.5	7.2	6.8	6.5																																
	横方向 (A)	縦方向 (B)	3.0	9.2	8.6	8.1	7.7	8.9	8.4	8.0	7.6	8.6	8.1	7.7	7.4	8.2	7.8	7.5	7.2	6.8																																
H m	1.27 H m	1.27 H m	4.0	9.5	9.0	8.6	8.3	9.3	8.9	8.5	8.1	8.9	8.5	8.2	7.9	8.5	8.2	8.0	7.7	7.3																																
			5.0	9.7	9.3	8.9	8.6	9.5	9.1	8.8	8.5	9.1	8.8	8.5	8.3	8.7	8.5	8.3	8.1	7.7	7.3																															
			7.0	9.9	9.6	9.3	9.1	9.7	9.4	9.2	9.0	9.3	9.1	8.9	8.7	9.0	8.8	8.6	8.5	8.0																																
			10.0	10.1	9.8	9.7	9.5	9.9	9.7	9.5	9.3	9.5	9.3	9.2	9.0	9.2	9.0	8.9	8.8	8.4																																

