

屋内照明器具特性

品番 (品名)	NTN88081B	
光源	LLD2020MLCB1 ×1	460.0 lm
管理番号	K0179234(0)DR1	
BZ分類	BZ1	

器具効率	98%	天井	80%				70%				50%				30%				0%	
	上方光束 1%		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	97%	床		10%				10%				10%				10%				0%
室指数	照明率 (X0.01)																			ZCM
保守率	良 0.69	0.6	79	73	69	66	79	72	68	66	77	72	68	66	76	71	68	65	64	
	中 0.67		0.8	85	79	75	72	84	79	75	72	83	78	74	72	81	77	74	72	70
	否 0.63		1.0	89	83	80	77	88	83	79	76	86	82	79	76	84	81	78	76	74
下方投影面積 等価発光面積	cm ²	1.25	92	87	84	81	91	86	83	80	89	85	82	80	87	84	81	79	78	
		1.5	94	90	86	84	93	89	86	83	91	88	85	83	89	86	84	82	80	
取付高さ	器具間隔最大限		2.5	99	95	93	91	97	95	92	90	95	93	91	89	93	91	89	88	86
	横方向 (A)	縦方向 (B)	3.0	100	97	95	93	99	96	94	92	96	94	92	91	94	92	91	90	87
Hm	0.45Hm	0.45Hm	4.0	101	99	97	95	100	98	96	95	98	96	95	93	95	94	93	92	89
			5.0	102	100	99	97	101	99	98	96	99	97	96	95	96	95	94	93	91
			7.0	103	102	101	99	102	101	100	98	100	99	98	97	97	96	96	95	92
			10.0	104	103	102	101	103	102	101	100	100	100	99	98	98	97	97	96	93

