

屋内照明器具特性

品番 (品名)	NTN88081B									
光源	LLD4000MLCE1 ×1					845.0 l m				
管理番号	K0179222 (0) DR 1									
BZ分類	BZ5									

器具効率	97 %	天井	80 %				70 %				50 %				30 %				0 %																																	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %																																	
		床	10 %				10 %				10 %				10 %				0 %																																	
上方光束	6 %	室指数																	照明率 (X0.01)																	ZCM																
下方光束	91 %																																																			
保守率	良 中 否	0.69	0.6	5.4	4.2	3.4	2.9	5.2	4.1	3.4	2.9	4.9	3.9	3.3	2.8	4.7	3.8	3.2	2.8	2.5																																
		0.67	0.8	6.3	5.2	4.4	3.9	6.1	5.1	4.4	3.8	5.8	4.9	4.2	3.8	5.5	4.7	4.1	3.7	3.4																																
			1.0	7.0	5.9	5.1	4.6	6.8	5.8	5.1	4.5	6.4	5.6	4.9	4.4	6.1	5.4	4.8	4.4	4.1																																
		0.63	1.25	7.5	6.6	5.8	5.3	7.3	6.4	5.8	5.2	6.9	6.2	5.6	5.1	6.6	6.0	5.4	5.0	4.7																																
下方投影面積	c m ²	1.5	7.9	7.0	6.4	5.8	7.7	6.9	6.3	5.8	7.3	6.6	6.1	5.6	7.0	6.4	5.9	5.5	5.2																																	
		2.0	8.5	7.7	7.1	6.6	8.3	7.6	7.0	6.5	7.9	7.3	6.8	6.4	7.5	7.0	6.6	6.3	5.9																																	
取付高さ	器具間隔最大限		2.5	8.8	8.2	7.6	7.2	8.6	8.0	7.5	7.1	8.2	7.7	7.3	6.9	7.8	7.4	7.1	6.8	6.4																																
	横方向 (A)	縦方向 (B)	3.0	9.1	8.5	8.0	7.6	8.9	8.3	7.9	7.5	8.5	8.0	7.6	7.3	8.1	7.7	7.4	7.1	6.8																																
H m	1.27 H m	1.27 H m	4.0	9.4	8.9	8.5	8.2	9.2	8.8	8.4	8.1	8.8	8.4	8.1	7.8	8.4	8.1	7.9	7.6	7.2																																
			5.0	9.6	9.2	8.8	8.5	9.4	9.0	8.7	8.4	9.0	8.7	8.4	8.2	8.6	8.4	8.2	8.0	7.6	7.2																															
			7.0	9.8	9.5	9.2	9.0	9.6	9.3	9.1	8.9	9.2	9.0	8.8	8.6	8.9	8.7	8.5	8.4	7.9																																
			10.0	10.0	9.7	9.6	9.4	9.8	9.6	9.4	9.2	9.4	9.2	9.1	8.9	9.1	8.9	8.8	8.7	8.2																																

