

屋内照明器具特性

品番 (品名)	L G W8 5 2 3 8 B	
光源	LLD3020LCE1 ×1	795.0 lm
管理番号	K0180442 (0) DR 1	
B Z 分類	B Z 5	

器具効率	47 %	天井	80 %				70 %				50 %				30 %				0 %		
	上方光束		4 %	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
	下方光束		43 %		床	10 %				10 %				10 %				10 %			
室指数	照明率 (X0.01)																				Z C M
保守率	良	0.63	0.6	2.5	1.9	1.6	1.3	2.4	1.9	1.5	1.3	2.3	1.8	1.5	1.3	2.1	1.7	1.5	1.2	1.1	
	中	0.6	0.8	2.9	2.4	2.0	1.7	2.9	2.3	2.0	1.7	2.7	2.2	1.9	1.7	2.5	2.1	1.9	1.6	1.5	
	否	0.56	1.0	3.2	2.7	2.3	2.1	3.1	2.7	2.3	2.0	3.0	2.5	2.2	2.0	2.8	2.4	2.2	1.9	1.8	
			1.25	3.5	3.0	2.7	2.4	3.4	3.0	2.6	2.3	3.2	2.8	2.5	2.3	3.0	2.7	2.4	2.2	2.1	
下方投影面積	c m ²		1.5	3.7	3.3	2.9	2.6	3.6	3.2	2.9	2.6	3.4	3.0	2.8	2.5	3.2	2.9	2.7	2.5	2.3	
	等価発光面積		c m ²	2.0	4.0	3.6	3.3	3.0	3.8	3.5	3.2	3.0	3.6	3.3	3.1	2.9	3.4	3.2	3.0	2.8	2.6
取付高さ	器具間隔最大限		2.5	4.1	3.8	3.5	3.3	4.0	3.7	3.4	3.2	3.8	3.5	3.3	3.1	3.6	3.4	3.2	3.0	2.8	
	横方向 (A)	縦方向 (B)	3.0	4.2	4.0	3.7	3.5	4.1	3.9	3.6	3.4	3.9	3.7	3.5	3.3	3.7	3.5	3.4	3.2	3.0	
H m	1.20 H m	1.19 H m	4.0	4.4	4.2	4.0	3.8	4.3	4.1	3.9	3.7	4.1	3.9	3.7	3.6	3.9	3.7	3.6	3.5	3.3	
			5.0	4.5	4.3	4.1	3.9	4.4	4.2	4.0	3.9	4.2	4.0	3.9	3.8	4.0	3.9	3.7	3.6	3.4	
			7.0	4.6	4.5	4.3	4.2	4.5	4.4	4.2	4.1	4.3	4.2	4.1	4.0	4.1	4.0	3.9	3.8	3.6	
			10.0	4.7	4.6	4.5	4.4	4.6	4.5	4.4	4.3	4.4	4.3	4.2	4.2	4.2	4.1	4.1	4.0	3.8	

