

屋内照明器具特性

品番 (品名)	L G W8 5 2 3 8 B	
光源	LLD20001CQ1 ×1	531.0 lm
管理番号	K0180444 (0) DR 1	
B Z 分類	B Z 5	

器具効率	53 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
		床	10 %				10 %				10 %				10 %				0 %	
上方光束	5 %																			
下方光束	48 %																			
室指数	照明率 (X0.01)																			ZCM
保守率	良 中 否	0.63	0.6	2.9	2.2	1.8	1.5	2.8	2.2	1.8	1.5	2.6	2.1	1.7	1.5	2.5	2.0	1.7	1.4	1.3
		0.6	0.8	3.4	2.8	2.3	2.0	3.3	2.7	2.3	2.0	3.1	2.6	2.2	2.0	2.9	2.5	2.2	1.9	1.8
			1.0	3.7	3.2	2.7	2.4	3.6	3.1	2.7	2.4	3.4	2.9	2.6	2.3	3.2	2.8	2.5	2.3	2.1
		0.56	1.25	4.0	3.5	3.1	2.8	3.9	3.4	3.0	2.8	3.7	3.3	2.9	2.7	3.5	3.1	2.8	2.6	2.4
下方投影面積	c m ²	1.5	4.3	3.8	3.4	3.1	4.1	3.7	3.3	3.0	3.9	3.5	3.2	2.9	3.7	3.3	3.1	2.9	2.7	
		2.0	4.6	4.1	3.8	3.5	4.4	4.0	3.7	3.5	4.2	3.9	3.6	3.3	3.9	3.7	3.4	3.2	3.0	
取付高さ	器具間隔最大限		2.5	4.7	4.4	4.1	3.8	4.6	4.3	4.0	3.7	4.4	4.1	3.8	3.6	4.1	3.9	3.7	3.5	3.3
	横方向 (A)	縦方向 (B)	3.0	4.9	4.6	4.3	4.0	4.7	4.4	4.2	4.0	4.5	4.2	4.0	3.8	4.3	4.1	3.9	3.7	3.5
H m	1.25 H m	1.25 H m	4.0	5.0	4.8	4.6	4.3	4.9	4.7	4.5	4.3	4.7	4.5	4.3	4.1	4.4	4.3	4.1	4.0	3.7
			5.0	5.2	4.9	4.7	4.6	5.0	4.8	4.6	4.5	4.8	4.6	4.5	4.3	4.5	4.4	4.3	4.2	3.9
			7.0	5.3	5.1	5.0	4.8	5.2	5.0	4.9	4.7	4.9	4.8	4.7	4.5	4.7	4.6	4.5	4.4	4.1
			10.0	5.4	5.3	5.1	5.0	5.3	5.1	5.0	4.9	5.0	4.9	4.8	4.7	4.8	4.7	4.6	4.6	4.3

