

# 屋内照明器具特性

品番 (品名)	NTN88081W	
光源	LLD3020MLCE1 ×1	795.0 lm
管理番号	K0179228(0)DR1	
BZ分類	BZ1	

器具効率	98%	天井	80%				70%				50%				30%				0%	
	上方光束 2%		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	96%	床		10%				10%				10%				10%				0%
室指数	照明率 (X0.01)																			ZCM
保守率	良 0.69	0.6	79	73	69	66	78	72	68	66	77	72	68	65	75	71	68	65	64	
	中 0.67		0.8	85	79	75	72	84	79	75	72	82	78	74	72	81	77	74	71	70
	否 0.63		1.0	89	83	79	77	88	83	79	76	86	81	78	76	84	80	77	75	74
下方投影面積	cm <sup>2</sup>	1.25	92	87	83	81	91	86	83	80	89	85	82	79	87	83	81	79	77	
		1.5	94	90	86	83	93	89	86	83	91	87	84	82	88	86	83	81	79	
等価発光面積	cm <sup>2</sup>	2.0	97	93	90	88	96	92	89	87	93	90	88	86	91	89	87	85	83	
		2.5	98	95	93	90	97	94	92	90	95	92	90	88	92	90	89	87	85	
取付高さ	器具間隔最大限		3.0	100	97	94	92	98	96	94	92	96	94	92	90	93	92	90	89	86
	横方向 (A)	縦方向 (B)	4.0	101	99	97	95	100	98	96	94	97	96	94	93	95	93	92	91	88
Hm	0.42Hm	0.42Hm	5.0	102	100	98	97	101	99	97	96	98	97	95	94	96	95	93	93	90
			7.0	103	102	100	99	102	100	99	98	99	98	97	96	97	96	95	94	91
			10.0	104	103	102	101	102	102	101	100	100	99	98	98	97	97	96	96	92

