

屋内照明器具特性

品番 (品名)	NTN88081W	
光源	LLD2020CU1 ×1	468.0 lm
管理番号	K0179219(0)DR1	
BZ分類	BZ1	

器具効率	98%	天井	80%				70%				50%				30%				0%	
	上方光束 0%		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	98%	床		10%				10%				10%				10%				0%
室指数	照明率 (X0.01)																			ZCM
保守率	良	0.69	0.6	81	75	71	68	80	75	71	68	79	74	70	68	78	73	70	68	67
	中	0.67	0.8	87	81	77	74	86	80	77	74	84	80	76	74	83	79	76	73	72
	否	0.63	1.0	90	85	81	78	89	84	81	78	87	83	80	78	86	82	79	77	76
下方投影面積	等価発光面積	cm ²	1.25	93	88	85	82	92	88	84	82	90	86	84	81	88	85	83	81	79
			1.5	95	91	88	85	94	90	87	85	92	89	86	84	90	87	85	83	81
取付高さ	器具間隔最大限		2.5	99	96	94	92	98	95	93	91	96	94	92	90	94	92	90	89	87
	横方向 (A)	縦方向 (B)	3.0	100	98	95	93	99	97	95	93	97	95	93	92	95	93	92	90	88
Hm	0.34Hm	0.34Hm	4.0	102	100	98	96	101	99	97	95	98	97	95	94	96	95	94	93	90
			5.0	103	101	99	98	101	100	98	97	99	98	97	95	97	96	95	94	91
			7.0	104	102	101	100	102	101	100	99	100	99	98	97	98	97	96	96	93
			10.0	104	103	103	102	103	102	101	101	100	99	99	99	98	97	97	94	

