

屋内照明器具特性

品番 (品名)	L G W8 5 2 3 9 B														
光源	LLD4300LCF1 ×1 930.0 l m														
管理番号	K0180426 (2) DR 1														
B Z 分類	B Z 6														

器具効率	72 %	天井	80 %				70 %				50 %				30 %				0 %			
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
上方光束	13 %	室指数	照明率 (X0.01)																			Z C M
下方光束	59 %																					
保守率	良 中 否 0.63 0.6 0.56	0.6	37	28	22	18	35	27	22	18	32	25	20	17	30	23	19	16	14			
		0.8	44	35	29	25	42	34	28	24	38	31	27	23	35	29	25	22	19			
		1.0	48	40	34	29	46	39	33	29	42	36	31	27	39	34	29	26	23			
		1.25	52	45	39	35	50	43	38	34	46	40	36	32	42	38	34	31	27			
下方投影面積	c m ²	1.5	55	48	43	38	53	47	42	37	49	43	39	36	45	40	37	34	30			
		2.0	59	53	48	44	57	52	47	43	53	48	44	41	49	45	42	39	35			
取付高さ	器具間隔最大限		2.5	62	57	52	48	60	55	51	47	55	51	48	45	51	48	45	42	38		
	横方向 (A)	縦方向 (B)	3.0	64	59	55	52	62	57	53	50	57	53	50	48	53	50	47	45	40		
H m	1.38 H m	1.38 H m	4.0	66	62	59	56	64	60	57	54	59	57	54	52	55	53	51	49	44		
			5.0	68	65	62	59	65	63	60	57	61	59	56	54	57	55	53	51	46		
			7.0	70	67	65	63	67	65	63	61	63	61	59	57	59	57	56	54	49		
			10.0	71	69	67	66	69	67	65	64	64	63	62	60	60	59	58	57	51		

