

| | |
|----------|-----------------------------|
| 屋内照明器具特性 | |
| 品番 (品名) | LGB81807 |
| 光源 | LED2700_70_630 x1 630.0 l m |
| 管理番号 | K0142373 (0) DR 1 |
| BZ分類 | BZ5 |

| | | | | | | | | | | | | | | | | | | | | |
|--------|---------|-----------------|--------------|----|----|----|-----|----|----|----|-----|----|----|----|-----|----|----|----|-----|----|
| 器具効率 | 100% | 天井 | 80% | | | | 70% | | | | 50% | | | | 30% | | | | 0% | |
| | | 壁 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0% | |
| 上方光束 | 50% | 床 | 10% | | | | 10% | | | | 10% | | | | 10% | | | | 0% | |
| 下方光束 | 50% | 室指数 | 照明率 (X0.01) | | | | | | | | | | | | | | | | ZCM | |
| 保守率 | 良 | 0.67 | 0.6 | 50 | 39 | 32 | 27 | 46 | 36 | 30 | 25 | 39 | 31 | 26 | 22 | 33 | 27 | 23 | 19 | 14 |
| | 中 | 0.63 | 0.8 | 59 | 48 | 40 | 35 | 54 | 45 | 38 | 33 | 46 | 39 | 33 | 29 | 38 | 33 | 29 | 26 | 19 |
| | 否 | 0.56 | 1.0 | 65 | 54 | 47 | 42 | 60 | 51 | 44 | 39 | 50 | 44 | 39 | 35 | 42 | 37 | 33 | 30 | 22 |
| | | | 1.25 | 70 | 61 | 54 | 48 | 65 | 57 | 50 | 46 | 55 | 49 | 44 | 40 | 46 | 41 | 37 | 34 | 26 |
| 下方投影面積 | | cm ² | 1.5 | 74 | 65 | 59 | 53 | 68 | 61 | 55 | 50 | 58 | 52 | 48 | 44 | 48 | 44 | 41 | 38 | 28 |
| 等価発光面積 | | cm ² | 2.0 | 79 | 72 | 66 | 61 | 73 | 67 | 62 | 57 | 62 | 57 | 53 | 50 | 52 | 48 | 45 | 43 | 32 |
| 取付高さ | 器具間隔最大限 | | 2.5 | 82 | 76 | 71 | 66 | 76 | 71 | 66 | 62 | 65 | 61 | 57 | 54 | 54 | 51 | 49 | 46 | 34 |
| | 横方向 (A) | 縦方向 (B) | 3.0 | 85 | 79 | 74 | 70 | 78 | 74 | 70 | 66 | 67 | 63 | 60 | 57 | 56 | 53 | 51 | 49 | 36 |
| 1.5m | 1.37m | 1.94m | 4.0 | 88 | 83 | 79 | 76 | 81 | 78 | 74 | 71 | 69 | 67 | 64 | 62 | 58 | 56 | 54 | 39 | |
| 2 | 1.58 | 2.56 | 5.0 | 89 | 86 | 82 | 79 | 83 | 80 | 77 | 74 | 71 | 69 | 66 | 64 | 60 | 58 | 56 | 41 | |
| 2.5 | 1.98 | 3.18 | 7.0 | 92 | 89 | 86 | 84 | 85 | 83 | 81 | 78 | 73 | 71 | 69 | 68 | 61 | 60 | 59 | 43 | |
| 3 | 2.36 | 3.8 | 10.0 | 93 | 91 | 89 | 87 | 87 | 85 | 83 | 82 | 75 | 73 | 72 | 71 | 63 | 62 | 61 | 45 | |

