

屋内照明器具特性	
品番 (品名)	S P L 5 4 2 9
光源	LLD4000LCE1 ×4                      845.0 l m
管理番号	K0183106 ( 0 ) DB 1
B Z 分類	B Z 5

器具効率	76 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	0 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	76 %	室指数	照明率 ( X 0.01 )																Z C M	
保守率	良	0.67	0.6	43	34	28	24	42	34	28	24	41	33	28	24	39	32	27	24	22
	中	0.63	0.8	51	42	36	32	50	42	36	32	48	41	36	32	46	40	35	32	30
	否	0.56	1.0	56	48	42	38	55	47	42	38	53	46	41	37	51	45	41	37	35
			1.25	61	53	48	44	59	53	47	43	57	51	47	43	55	50	46	43	41
下方投影面積	c m <sup>2</sup>		1.5	64	57	52	48	63	56	52	48	60	55	51	47	58	54	50	47	45
	等価発光面積		c m <sup>2</sup>	2.0	68	63	58	54	67	62	58	54	65	60	56	53	62	59	56	53
取付高さ	器具間隔最大限		2.5	71	66	62	59	70	65	61	58	67	64	60	58	65	62	59	57	55
	横方向 ( A )	縦方向 ( B )	3.0	73	69	65	62	72	68	64	61	69	66	63	61	67	64	62	60	58
H m	1.27 H m	1.27 H m	4.0	75	72	69	66	74	71	68	66	72	69	67	65	70	68	66	64	62
			5.0	77	74	71	69	75	73	71	69	73	71	69	67	71	70	68	66	64
			7.0	78	76	74	73	77	75	74	72	75	74	72	71	73	72	71	70	67
			10.0	79	78	77	75	78	77	76	75	77	75	74	73	75	74	73	72	70

