

# 屋内照明器具特性

品番 (品名)	P M L E L 1 2 0 2 7 F C														
光源	LED2700_70_2920 x1 2920.0 1 m														
管理番号	K0176989 ( 0 ) DY 1														
B Z 分類	B Z 5 / 0.7 / B Z 4														

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束	2 %	反射率	床	10 %				10 %				10 %				10 %				0 %
下方光束	98 %		室指数	照明率 ( X 0.01 )																Z C M
保守率	良	0.69	0.6	5.8	4.6	3.9	3.3	5.7	4.6	3.8	3.3	5.4	4.4	3.8	3.3	5.2	4.3	3.7	3.3	3.1
	中	0.67	0.8	6.8	5.7	5.0	4.4	6.7	5.6	4.9	4.4	6.4	5.5	4.8	4.4	6.1	5.3	4.8	4.3	4.1
	否	0.63	1.0	7.5	6.5	5.7	5.2	7.3	6.4	5.7	5.2	7.0	6.2	5.6	5.1	6.7	6.0	5.5	5.0	4.8
			1.25	8.1	7.2	6.5	5.9	7.9	7.1	6.4	5.9	7.6	6.9	6.3	5.8	7.3	6.7	6.2	5.8	5.5
下方投影面積			1.5	8.5	7.6	7.0	6.5	8.3	7.5	6.9	6.4	8.0	7.3	6.8	6.4	7.7	7.1	6.7	6.3	6.0
等価発光面積			2.0	9.0	8.3	7.8	7.3	8.8	8.2	7.7	7.2	8.5	8.0	7.5	7.1	8.2	7.7	7.4	7.0	6.7
取付高さ	器具間隔最大限		2.5	9.4	8.8	8.3	7.8	9.2	8.6	8.2	7.8	8.8	8.4	8.0	7.7	8.5	8.2	7.8	7.5	7.2
	横方向 (A)	縦方向 (B)	3.0	9.6	9.1	8.6	8.2	9.4	8.9	8.5	8.2	9.1	8.7	8.3	8.0	8.8	8.4	8.2	7.9	7.6
1.5m	1.9m	2.13m	4.0	9.9	9.5	9.1	8.8	9.7	9.3	9.0	8.7	9.4	9.1	8.8	8.5	9.1	8.8	8.6	8.4	8.1
2	2.51	2.69	5.0	10.0	9.7	9.4	9.1	9.9	9.6	9.3	9.0	9.6	9.3	9.1	8.9	9.3	9.1	8.9	8.7	8.4
2.5	3.13	3.27	7.0	10.3	10.0	9.8	9.6	10.1	9.9	9.7	9.5	9.8	9.6	9.4	9.2	9.5	9.3	9.2	9.0	8.7
3	3.74	3.86	10.0	10.4	10.2	10.1	9.9	10.3	10.1	9.9	9.8	10.0	9.8	9.7	9.6	9.7	9.6	9.4	9.3	9.0

