

屋内照明器具特性

品番 (品名)	NTN88081W	
光源	LLD3020MLCB1 ×1	715.0 lm
管理番号	K0179230(0)DR1	
BZ分類	BZ1	

器具効率	98%	天井	80%				70%				50%				30%				0%	
	上方光束 2%		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	96%	床		10%				10%				10%				10%				0%
室指数	照明率 (X0.01)																			ZCM
保守率	良 0.69	0.6	79	72	68	65	78	71	67	65	76	71	67	64	75	70	67	64	63	
	中 0.67		0.8	84	78	74	71	83	78	74	71	82	77	73	71	80	76	73	70	69
	否 0.63		1.0	88	83	79	76	87	82	78	75	85	81	77	75	83	80	77	74	73
下方投影面積 等価発光面積	cm ²	1.25	91	86	83	80	90	86	82	79	88	84	81	79	86	83	80	78	76	
		1.5	94	89	86	83	92	88	85	82	90	87	84	82	88	85	83	81	79	
取付高さ	器具間隔最大限		2.5	98	95	92	90	97	94	91	89	94	92	90	88	92	90	88	87	84
	横方向 (A)	縦方向 (B)	3.0	99	97	94	92	98	95	93	91	96	93	92	90	93	91	90	89	86
Hm	0.43Hm	0.43Hm	4.0	101	99	97	95	99	97	96	94	97	95	94	92	95	93	92	91	88
			5.0	102	100	98	97	100	99	97	96	98	96	95	94	95	94	93	92	89
			7.0	103	101	100	99	101	100	99	98	99	98	97	96	96	95	94	91	
			10.0	104	103	102	101	102	101	100	100	100	99	98	97	97	96	95	92	

