

屋内照明器具特性

品番 (品名)	NTN88081W									
光源	LLD2000CU1 x1					566.0 lm				
管理番号	K0179215(0)DR1									
BZ分類	BZ5									

器具効率	97%	天井	80%				70%				50%				30%				0%		
	上方光束		6%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		91%		床	10%				10%				10%				10%			
室指数	照明率 (X0.01)																			ZCM	
保守率	良	0.69	0.6	5.3	4.1	3.4	2.9	5.2	4.1	3.3	2.8	4.9	3.9	3.3	2.8	4.6	3.8	3.2	2.7	2.5	
	中	0.67	0.8	6.3	5.2	4.4	3.8	6.1	5.1	4.3	3.8	5.8	4.9	4.2	3.7	5.5	4.7	4.1	3.6	3.4	
	否	0.63	1.0	6.9	5.9	5.1	4.5	6.7	5.7	5.0	4.5	6.4	5.5	4.9	4.4	6.0	5.3	4.7	4.3	4.0	
	下方投影面積	c m ²		1.25	7.5	6.5	5.8	5.2	7.3	6.4	5.7	5.2	6.9	6.1	5.5	5.1	6.5	5.9	5.4	5.0	4.7
取付高さ	器具間隔最大限		2.5	8.8	8.1	7.6	7.1	8.6	8.0	7.5	7.0	8.2	7.7	7.2	6.9	7.8	7.4	7.0	6.7	6.3	
	横方向 (A)	縦方向 (B)																			
H m	1.28 H m	1.28 H m	4.0	9.4	8.9	8.5	8.1	9.1	8.7	8.3	8.0	8.7	8.4	8.1	7.8	8.4	8.1	7.8	7.6	7.2	
			5.0	9.5	9.2	8.8	8.5	9.3	9.0	8.7	8.4	8.9	8.6	8.4	8.1	8.6	8.3	8.1	7.9	7.5	
			7.0	9.8	9.5	9.2	9.0	9.6	9.3	9.1	8.8	9.2	9.0	8.8	8.6	8.8	8.6	8.5	8.3	7.9	
			10.0	9.9	9.7	9.5	9.3	9.7	9.5	9.4	9.2	9.4	9.2	9.0	8.9	9.0	8.9	8.7	8.6	8.2	

