

屋内照明器具特性	
品番 (品名)	LGB81788
光源	LED2700_70_2200 x1 2200.0 1m
管理番号	K0142372(0)DR1
BZ分類	BZ10

器具効率	100%	反射率	天井	80%				70%				50%				30%				0%	
	上方光束		100%	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		0%	床	10%				10%				10%				10%				0%
		室指数	照明率 ( X0.01 )																ZCM		
保守率	良	0.69	0.6	43	33	26	22	37	28	23	19	25	19	16	13	14	11	9	8	0	
	中	0.67	0.8	51	41	34	29	43	35	29	25	29	24	21	18	17	14	12	10	0	
	否	0.63	1.0	56	47	40	35	48	40	35	31	33	28	24	22	19	16	14	13	0	
			1.25	61	53	46	42	52	46	40	36	36	31	28	25	20	18	16	15	0	
下方投影面積	cm <sup>2</sup>		1.5	65	57	51	46	56	49	44	40	38	34	31	28	22	20	18	17	0	
等価発光面積	cm <sup>2</sup>		2.0	70	63	58	54	60	55	50	47	41	38	35	33	24	22	21	19	0	
取付高さ	器具間隔最大限		2.5	73	67	63	59	63	58	54	51	43	40	38	36	25	23	22	21	0	
	横方向 (A)	縦方向 (B)																			
1.5m	0.3m	0.3m	3.0	75	70	66	62	64	61	57	54	44	42	40	38	26	24	23	22	0	
2	0.4	0.4	4.0	78	74	70	67	67	64	61	58	46	44	43	41	27	26	25	24	0	
2.5	0.5	0.5	5.0	79	76	73	71	68	66	63	61	47	46	44	43	27	27	26	25	0	
3	0.6	0.6	7.0	81	79	77	75	70	68	66	65	49	47	46	45	28	28	27	27	0	
			10.0	83	81	80	78	72	70	69	68	50	49	48	47	29	28	28	28	0	

