

屋内照明器具特性	
品番 (品名)	P M L E L 0 4 8 2 7 N S
光源	LED2700_70_1150 x1 1150.0 lm
管理番号	K0177198 (0) DY 1
B Z 分類	BZ2 / 1.1 / BZ3 / 6.0 / BZ4

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束	5 %	反射率	床	10 %				10 %				10 %				10 %				0 %
下方光束	95 %		室指数	照明率 (X0.01)																ZCM
保守率	良 中 否	0.69	0.6	66	57	50	46	65	56	50	46	63	55	49	45	60	53	48	45	43
		0.67	0.8	75	66	60	55	73	65	59	55	71	63	58	54	68	62	57	54	51
			1.0	80	72	66	61	79	71	65	61	76	69	64	60	73	67	63	59	57
		0.63	1.25	85	78	72	67	83	76	71	67	80	74	70	66	77	72	68	65	62
下方投影面積	c m ²	1.5	88	81	76	72	87	80	75	71	83	78	74	70	80	76	72	69	66	
		2.0	93	87	82	78	91	86	81	78	87	83	79	76	84	81	77	75	72	
取付高さ	器具間隔最大限		2.5	95	90	86	83	93	89	85	82	90	86	83	80	87	84	81	78	75
	横方向 (A)	縦方向 (B)	3.0	97	93	89	86	95	91	88	85	92	89	86	83	89	86	83	81	78
1.5m	1 m	1.72 m	4.0	99	96	93	90	98	94	92	89	94	92	89	87	91	89	87	85	81
2	1.32	2.27	5.0	101	98	95	93	99	96	94	92	96	93	91	90	92	91	89	87	84
2.5	1.59	2.81	7.0	103	100	98	96	101	99	97	95	97	96	94	93	94	93	92	90	86
3	1.91	3.38	10.0	104	102	101	99	102	101	99	98	99	98	96	95	96	95	94	93	89

