

屋内照明器具特性

品番 (品名)	LGB81820															
光源	LED5000_70_2650 x1 2650.0 1m															
管理番号	K0142374(0)DR1															
BZ分類	BZ6															

器具効率	100%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	50%	反射率	床	10%				10%				10%				10%				0%
下方光束	50%		室指数	照明率 (X0.01) ZCM																
保守率	良 中 否	0.67	0.6	48	36	29	23	44	34	27	22	37	29	23	19	30	24	20	16	11
		0.63	0.8	56	45	37	32	52	42	35	30	43	36	30	26	36	30	25	22	16
			1.0	62	52	44	38	57	48	41	36	48	41	35	31	40	34	30	26	19
		0.56	1.25	68	58	50	45	62	54	47	42	52	46	41	36	43	38	34	31	22
下方投影面積	c m ²	1.5	72	63	55	50	66	58	52	47	56	49	44	40	46	41	37	34	24	
		2.0	77	69	63	57	71	64	59	54	60	55	50	46	50	46	42	39	28	
取付高さ	器具間隔最大限		2.5	81	74	68	63	74	68	63	59	63	58	54	51	52	49	46	43	31
	横方向 (A)	縦方向 (B)	3.0	83	77	72	67	77	71	67	63	65	61	57	54	54	51	48	46	33
1.5m	1.25m	2.19m	4.0	86	81	77	73	80	75	71	68	68	64	61	59	56	54	52	49	36
2	1.67	2.77	5.0	88	84	80	77	82	78	75	71	69	67	64	62	58	56	54	52	38
2.5	2.08	3.38	7.0	90	87	84	81	84	81	78	76	72	69	67	65	60	58	57	55	40
3	2.5	4.01	10.0	92	90	88	85	86	84	82	80	73	72	70	69	62	60	59	58	42

