

屋内照明器具特性

品番 (品名)	L G W 5 1 7 6 9 W	
光源	LLD4000LCE1 ×1	845.0 l m
管理番号	K0181592 (0) DR 1	
B Z 分類	B Z 5	

器具効率	83 %	天井	80 %				70 %				50 %				30 %				0 %		
	上方光束		13 %	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
	下方光束		70 %		床	10 %				10 %				10 %				10 %			
室指数	照明率 (X 0 . 0 1)																				Z C M
保守率	良	0.63	0.6	4.4	3.4	2.7	2.3	4.2	3.3	2.7	2.2	3.9	3.1	2.5	2.2	3.6	2.9	2.4	2.1	1.8	
	中	0.6	0.8	5.2	4.2	3.5	3.1	5.0	4.1	3.5	3.0	4.6	3.9	3.3	2.9	4.3	3.6	3.2	2.8	2.5	
	否	0.56	1.0	5.7	4.8	4.1	3.7	5.5	4.7	4.0	3.6	5.1	4.4	3.9	3.4	4.7	4.1	3.7	3.3	3.0	
	下方投影面積	c m ²		1.25	6.2	5.4	4.7	4.2	6.0	5.2	4.6	4.2	5.5	4.9	4.4	4.0	5.1	4.6	4.2	3.8	3.5
等価発光面積	c m ²		1.5	6.5	5.8	5.2	4.7	6.3	5.6	5.1	4.6	5.9	5.3	4.8	4.4	5.4	5.0	4.6	4.2	3.8	
	c m ²		2.0	7.0	6.4	5.8	5.4	6.8	6.2	5.7	5.3	6.3	5.8	5.4	5.0	5.9	5.5	5.1	4.8	4.4	
取付高さ	器具間隔最大限		2.5	7.3	6.7	6.3	5.9	7.1	6.5	6.1	5.7	6.6	6.2	5.8	5.5	6.1	5.8	5.5	5.2	4.8	
	横方向 (A)	縦方向 (B)	3.0	7.5	7.0	6.6	6.2	7.3	6.8	6.4	6.1	6.8	6.4	6.1	5.8	6.3	6.0	5.8	5.5	5.0	
H m	1.30 H m	1.30 H m	4.0	7.8	7.4	7.0	6.7	7.5	7.2	6.8	6.5	7.1	6.8	6.5	6.2	6.6	6.4	6.1	5.9	5.4	
			5.0	7.9	7.6	7.3	7.0	7.7	7.4	7.1	6.9	7.2	7.0	6.7	6.5	6.8	6.6	6.4	6.2	5.7	
			7.0	8.1	7.9	7.6	7.4	7.9	7.7	7.4	7.2	7.4	7.2	7.1	6.9	7.0	6.8	6.7	6.5	6.0	
			10.0	8.3	8.1	7.9	7.8	8.0	7.9	7.7	7.6	7.6	7.4	7.3	7.2	7.1	7.0	6.9	6.8	6.2	

