

屋内照明器具特性

品番 (品名)	L G W 5 1 7 6 9 Y				
光源	LLD4000MLCE1 ×1		845.0 l m		
管理番号	K0182067 (0) DR 1				
B Z 分類	B Z 5				

器具効率	82 %	天井	80 %				70 %				50 %				30 %				0 %		
	上方光束		12 %	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
	下方光束		70 %		床	10 %				10 %				10 %				10 %			
室指数	照明率 (X 0 . 0 1)																			Z C M	
保守率	良	0.63	0.6	43	33	27	23	42	32	26	22	39	31	25	21	36	29	24	21	18	
	中	0.6	0.8	51	42	35	30	49	40	34	30	46	38	33	29	42	36	31	28	25	
	否	0.56	1.0	57	48	41	36	54	46	40	36	50	43	38	34	47	41	36	33	30	
			1.25	61	53	47	42	59	52	46	41	55	49	44	40	51	46	42	38	35	
下方投影面積	c m ²		1.5	65	57	51	47	62	55	50	46	58	52	48	44	54	49	45	42	38	
	等価発光面積		c m ²	2.0	69	63	58	53	67	61	56	52	62	57	53	50	58	54	51	48	44
取付高さ	器具間隔最大限		2.5	72	67	62	58	70	65	60	57	65	61	57	54	61	57	54	52	47	
	横方向 (A)	縦方向 (B)	3.0	74	69	65	61	72	67	63	60	67	64	60	57	63	60	57	55	50	
H m	1.30 H m	1.30 H m	4.0	77	73	69	66	74	71	68	65	70	67	64	62	65	63	61	59	54	
			5.0	78	75	72	69	76	73	70	68	71	69	67	65	67	65	63	62	56	
			7.0	80	78	76	73	78	76	74	72	73	72	70	68	69	68	66	65	60	
			10.0	82	80	78	77	80	78	76	75	75	74	72	71	71	70	69	67	62	

