

# 屋内照明器具特性

品番 (品名)	L G W 5 1 7 6 9 Y				
光源	LLD2000LCE1 ×1                      531.0 l m				
管理番号	K0181590 ( 0 ) DR 1				
B Z 分類	B Z 5				

器具効率	83 %	天井	80 %				70 %				50 %				30 %				0 %		
	上方光束		12 %	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
	下方光束		71 %		床	10 %				10 %				10 %				10 %			
室指数	照明率 ( X 0 . 0 1 )																				Z C M
保守率	良	0.63	0.6	4.4	3.4	2.7	2.3	4.2	3.3	2.7	2.3	3.9	3.1	2.6	2.2	3.6	2.9	2.5	2.1	1.9	
	中	0.6	0.8	5.2	4.2	3.6	3.1	5.0	4.1	3.5	3.0	4.6	3.9	3.3	2.9	4.3	3.7	3.2	2.8	2.5	
	否	0.56	1.0	5.7	4.8	4.2	3.7	5.5	4.7	4.1	3.6	5.1	4.4	3.9	3.5	4.8	4.2	3.7	3.3	3.0	
	下方投影面積	c m <sup>2</sup>		1.25	6.2	5.4	4.8	4.3	6.0	5.2	4.7	4.2	5.6	4.9	4.4	4.0	5.2	4.6	4.2	3.9	3.5
取付高さ	器具間隔最大限		H m	2.5	7.3	6.8	6.3	5.9	7.1	6.6	6.1	5.8	6.6	6.2	5.8	5.5	6.2	5.8	5.5	4.8	
	横方向 ( A )	縦方向 ( B )		3.0	7.5	7.0	6.6	6.2	7.3	6.8	6.4	6.1	6.8	6.5	6.1	5.8	6.4	6.1	5.8	5.1	
等価発光面積	c m <sup>2</sup>		H m	4.0	7.8	7.4	7.0	6.7	7.6	7.2	6.9	6.6	7.1	6.8	6.5	6.3	6.7	6.4	6.2	6.0	
	c m <sup>2</sup>			5.0	8.0	7.6	7.3	7.1	7.7	7.4	7.1	6.9	7.3	7.0	6.8	6.6	6.8	6.6	6.4	6.3	
	c m <sup>2</sup>			7.0	8.2	7.9	7.7	7.5	7.9	7.7	7.5	7.3	7.5	7.3	7.1	6.9	7.0	6.9	6.7	6.6	
	c m <sup>2</sup>			10.0	8.3	8.1	7.9	7.8	8.1	7.9	7.7	7.6	7.6	7.5	7.3	7.2	7.2	7.1	7.0	6.9	

