

# 屋内照明器具特性

品番 (品名)	XLGE5008	
光源	LLD2000VCE1 ×1	531.0 lm
管理番号	K0181590(0)DR1	
BZ分類	BZ5	

器具効率	83%	天井	80%				70%				50%				30%				0%		
	上方光束		12%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		71%		床	10%				10%				10%				10%			
室指数	照明率 ( X0.01 )																			ZCM	
保守率	良	0.63	0.6	4.4	3.4	2.7	2.3	4.2	3.3	2.7	2.3	3.9	3.1	2.6	2.2	3.6	2.9	2.5	2.1	1.9	
	中	0.6	0.8	5.2	4.2	3.6	3.1	5.0	4.1	3.5	3.0	4.6	3.9	3.3	2.9	4.3	3.7	3.2	2.8	2.5	
	否	0.56	1.0	5.7	4.8	4.2	3.7	5.5	4.7	4.1	3.6	5.1	4.4	3.9	3.5	4.8	4.2	3.7	3.3	3.0	
	下方投影面積	c m <sup>2</sup>		1.25	6.2	5.4	4.8	4.3	6.0	5.2	4.7	4.2	5.6	4.9	4.4	4.0	5.2	4.6	4.2	3.9	3.5
取付高さ	器具間隔最大限		1.5	6.6	5.8	5.2	4.7	6.3	5.6	5.1	4.6	5.9	5.3	4.8	4.5	5.5	5.0	4.6	4.3	3.9	
	横方向 (A)	縦方向 (B)	2.0	7.0	6.4	5.9	5.4	6.8	6.2	5.7	5.3	6.3	5.8	5.4	5.1	5.9	5.5	5.2	4.9	4.4	
H m	1.29 H m	1.29 H m	2.5	7.3	6.8	6.3	5.9	7.1	6.6	6.1	5.8	6.6	6.2	5.8	5.5	6.2	5.8	5.5	5.3	4.8	
			3.0	7.5	7.0	6.6	6.2	7.3	6.8	6.4	6.1	6.8	6.5	6.1	5.8	6.4	6.1	5.8	5.6	5.1	
			4.0	7.8	7.4	7.0	6.7	7.6	7.2	6.9	6.6	7.1	6.8	6.5	6.3	6.7	6.4	6.2	6.0	5.5	
			5.0	8.0	7.6	7.3	7.1	7.7	7.4	7.1	6.9	7.3	7.0	6.8	6.6	6.8	6.6	6.4	6.3	5.7	
			7.0	8.2	7.9	7.7	7.5	7.9	7.7	7.5	7.3	7.5	7.3	7.1	6.9	7.0	6.9	6.7	6.6	6.1	
			10.0	8.3	8.1	7.9	7.8	8.1	7.9	7.7	7.6	7.6	7.5	7.3	7.2	7.2	7.1	7.0	6.9	6.3	

