

屋内照明器具特性

| | | |
|---------|-----------------------------|----------|
| 品番 (品名) | XLGE5112 | |
| 光源 | LLD4000VCE1 ×1 | 845.0 lm |
| 管理番号 | K0181604(0)DR1 | |
| BZ分類 | BZ5/1.1/BZ4/6.0/BZ5/8.5/BZ4 | |

| | | | | | | | | | | | | | | | | | | | | |
|--------|------------------|------------------|------|------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| 器具効率 | 69% | 天井 | 80% | | | | 70% | | | | 50% | | | | 30% | | | | 0% | |
| | 上方光束 0% | | 反射率 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0% |
| 下方光束 | 69% | 床 | | 10% | | | | 10% | | | | 10% | | | | 10% | | | | 0% |
| 室指数 | 照明率 (X0.01) | | | | | | | | | | | | | | | | | | | ZCM |
| 保守率 | 良 | 0.63 | 0.6 | 3.9 | 3.1 | 2.6 | 2.2 | 3.9 | 3.1 | 2.6 | 2.2 | 3.7 | 3.0 | 2.5 | 2.2 | 3.5 | 2.9 | 2.5 | 2.2 | 2.1 |
| | 中 | 0.6 | 0.8 | 4.6 | 3.9 | 3.3 | 2.9 | 4.5 | 3.8 | 3.3 | 2.9 | 4.3 | 3.7 | 3.3 | 2.9 | 4.2 | 3.6 | 3.2 | 2.9 | 2.8 |
| | 否 | 0.56 | 1.0 | 5.1 | 4.4 | 3.8 | 3.5 | 5.0 | 4.3 | 3.8 | 3.4 | 4.8 | 4.2 | 3.8 | 3.4 | 4.6 | 4.1 | 3.7 | 3.4 | 3.3 |
| | 下方投影面積 | c m ² | | 1.25 | 5.5 | 4.8 | 4.4 | 4.0 | 5.4 | 4.8 | 4.3 | 4.0 | 5.2 | 4.7 | 4.3 | 3.9 | 5.0 | 4.5 | 4.2 | 3.9 |
| 等価発光面積 | c m ² | | 1.5 | 5.8 | 5.2 | 4.7 | 4.4 | 5.7 | 5.1 | 4.7 | 4.3 | 5.5 | 5.0 | 4.6 | 4.3 | 5.3 | 4.9 | 4.5 | 4.3 | 4.1 |
| | c m ² | | 2.0 | 6.2 | 5.7 | 5.3 | 4.9 | 6.0 | 5.6 | 5.2 | 4.9 | 5.8 | 5.5 | 5.1 | 4.8 | 5.6 | 5.3 | 5.0 | 4.8 | 4.6 |
| 取付高さ | 器具間隔最大限 | | 2.5 | 6.4 | 6.0 | 5.6 | 5.3 | 6.3 | 5.9 | 5.6 | 5.3 | 6.1 | 5.8 | 5.5 | 5.2 | 5.9 | 5.6 | 5.4 | 5.2 | 5.0 |
| | 横方向 (A) | 縦方向 (B) | 3.0 | 6.6 | 6.2 | 5.9 | 5.6 | 6.5 | 6.1 | 5.8 | 5.6 | 6.3 | 6.0 | 5.7 | 5.5 | 6.1 | 5.8 | 5.6 | 5.4 | 5.2 |
| H m | 1.23 H m | 1.23 H m | 4.0 | 6.8 | 6.5 | 6.2 | 6.0 | 6.7 | 6.4 | 6.2 | 6.0 | 6.5 | 6.3 | 6.0 | 5.9 | 6.3 | 6.1 | 5.9 | 5.8 | 5.6 |
| | | | 5.0 | 6.9 | 6.7 | 6.4 | 6.2 | 6.8 | 6.6 | 6.4 | 6.2 | 6.6 | 6.4 | 6.3 | 6.1 | 6.4 | 6.3 | 6.1 | 6.0 | 5.8 |
| | | | 7.0 | 7.0 | 6.9 | 6.7 | 6.6 | 7.0 | 6.8 | 6.6 | 6.5 | 6.8 | 6.6 | 6.5 | 6.4 | 6.6 | 6.5 | 6.4 | 6.3 | 6.1 |
| | | | 10.0 | 7.2 | 7.0 | 6.9 | 6.8 | 7.1 | 6.9 | 6.8 | 6.7 | 6.9 | 6.8 | 6.7 | 6.6 | 6.7 | 6.6 | 6.6 | 6.5 | 6.3 |

