

屋内照明器具特性

品番 (品名)	XLGE5119	
光源	LLD4000NCE1 ×1	845.0 lm
管理番号	K0181607(0)DR1	
BZ分類	BZ5/0.9/BZ4/6.0/BZ5/8.5/BZ4	

器具効率	65%	天井	80%				70%				50%				30%				0%		
	上方光束		0%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		65%		床	10%				10%				10%				10%			
室指数	照明率 (X0.01)																				ZCM
保守率	良	0.63	0.6	0.6	3.7	3.0	2.5	2.1	3.7	2.9	2.4	2.1	3.5	2.9	2.4	2.1	3.4	2.8	2.4	2.1	2.0
	中	0.6	0.6	0.6	4.4	3.7	3.2	2.8	4.3	3.6	3.1	2.8	4.1	3.5	3.1	2.8	4.0	3.4	3.1	2.8	2.6
	否	0.56	0.56	0.56	4.8	4.1	3.7	3.3	4.7	4.1	3.6	3.3	4.5	4.0	3.6	3.3	4.4	3.9	3.5	3.2	3.1
					1.25	5.2	4.6	4.1	3.8	5.1	4.5	4.1	3.8	4.9	4.4	4.0	3.7	4.7	4.3	4.0	3.7
下方投影面積	c m ²		1.5	5.5	4.9	4.5	4.1	5.4	4.9	4.4	4.1	5.2	4.7	4.4	4.1	5.0	4.6	4.3	4.0	3.9	
	等価発光面積		c m ²	2.0	5.8	5.4	5.0	4.7	5.7	5.3	4.9	4.7	5.5	5.2	4.9	4.6	5.4	5.0	4.8	4.5	4.4
取付高さ	器具間隔最大限		2.5	6.1	5.7	5.3	5.0	6.0	5.6	5.3	5.0	5.8	5.5	5.2	5.0	5.6	5.3	5.1	4.9	4.7	
	横方向 (A)	縦方向 (B)	3.0	6.2	5.9	5.6	5.3	6.1	5.8	5.5	5.3	5.9	5.7	5.4	5.2	5.8	5.5	5.3	5.1	5.0	
H m	1.22 H m	1.22 H m	4.0	6.4	6.1	5.9	5.7	6.3	6.1	5.8	5.6	6.1	5.9	5.7	5.6	6.0	5.8	5.6	5.5	5.3	
			5.0	6.5	6.3	6.1	5.9	6.4	6.2	6.0	5.9	6.3	6.1	5.9	5.8	6.1	6.0	5.8	5.7	5.5	
			7.0	6.7	6.5	6.4	6.2	6.6	6.4	6.3	6.2	6.4	6.3	6.2	6.1	6.3	6.1	6.0	5.9	5.8	
			10.0	6.8	6.7	6.6	6.4	6.7	6.6	6.5	6.4	6.5	6.4	6.4	6.3	6.4	6.3	6.2	6.2	6.0	

