

# 屋内照明器具特性

|         |                   |  |          |  |  |
|---------|-------------------|--|----------|--|--|
| 品番 (品名) | XAD3 100LK        |  |          |  |  |
| 光源      | LLD4000LCB1 ×1    |  | 845.0 lm |  |  |
| 管理番号    | K0175549 (0) DR 1 |  |          |  |  |
| BZ分類    | BZ4 / 0.7 / BZ3   |  |          |  |  |

|        |                  |          |                  |     |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     |    |
|--------|------------------|----------|------------------|-----|----|----|------|----|----|----|------|----|----|----|------|----|----|----|-----|----|
| 器具効率   | 83 %             | 天井       | 80 %             |     |    |    | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |    |
|        |                  | 壁        | 70               | 50  | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |    |
| 上方光束   | 0 %              | 床        | 10 %             |     |    |    | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |    |
| 下方光束   | 83 %             | 室指数      | 照明率 ( X0.01 )    |     |    |    |      |    |    |    |      |    |    |    |      |    |    |    | ZCM |    |
| 保守率    | 良                | 0.67     | 0.6              | 51  | 41 | 35 | 31   | 50 | 41 | 35 | 31   | 48 | 40 | 35 | 31   | 46 | 39 | 34 | 31  | 29 |
|        | 中                | 0.63     | 0.8              | 59  | 51 | 45 | 41   | 58 | 50 | 45 | 41   | 56 | 49 | 44 | 40   | 54 | 48 | 44 | 40  | 39 |
|        | 否                | 0.56     | 1.0              | 65  | 57 | 52 | 48   | 64 | 57 | 51 | 47   | 62 | 55 | 51 | 47   | 60 | 54 | 50 | 47  | 45 |
|        |                  |          | 1.25             | 70  | 63 | 58 | 54   | 69 | 62 | 57 | 54   | 66 | 61 | 57 | 53   | 64 | 60 | 56 | 53  | 51 |
| 下方投影面積 | c m <sup>2</sup> |          | 1.5              | 73  | 67 | 62 | 58   | 72 | 66 | 62 | 58   | 69 | 65 | 61 | 58   | 67 | 63 | 60 | 57  | 55 |
|        | 等価発光面積           |          | c m <sup>2</sup> | 2.0 | 77 | 72 | 68   | 65 | 76 | 71 | 67   | 64 | 74 | 70 | 66   | 64 | 72 | 68 | 65  | 63 |
| 取付高さ   | 器具間隔最大限          |          | 2.5              | 80  | 75 | 72 | 69   | 78 | 75 | 71 | 68   | 76 | 73 | 70 | 68   | 74 | 71 | 69 | 67  | 65 |
|        | 横方向 (A)          | 縦方向 (B)  | 3.0              | 81  | 78 | 75 | 72   | 80 | 77 | 74 | 71   | 78 | 75 | 73 | 70   | 76 | 74 | 71 | 70  | 68 |
| H m    | 1.25 H m         | 1.25 H m | 4.0              | 83  | 81 | 78 | 76   | 82 | 80 | 77 | 75   | 80 | 78 | 76 | 74   | 78 | 76 | 75 | 73  | 71 |
|        |                  |          | 5.0              | 85  | 82 | 80 | 78   | 84 | 81 | 79 | 78   | 81 | 80 | 78 | 76   | 79 | 78 | 77 | 75  | 73 |
|        |                  |          | 7.0              | 86  | 84 | 83 | 81   | 85 | 83 | 82 | 81   | 83 | 82 | 80 | 79   | 81 | 80 | 79 | 78  | 76 |
|        |                  |          | 10.0             | 87  | 86 | 85 | 84   | 86 | 85 | 84 | 83   | 84 | 83 | 82 | 81   | 82 | 81 | 81 | 80  | 78 |

