

# 屋内照明器具特性

品番 (品名)	XAD3 100 VK				
光源	LLD4000VCB1 ×1		845.0 lm		
管理番号	K0175549 (0) DR 1				
BZ分類	BZ4 / 0.7 / BZ3				

器具効率	83 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
		床	10 %				10 %				10 %				10 %				0 %	
上方光束	0 %	室指数																		
下方光束	83 %	照明率 ( X0.01 )																		
		ZCM																		
保守率	良 中 否	0.67	0.6	51	41	35	31	50	41	35	31	48	40	35	31	46	39	34	31	29
		0.63	0.8	59	51	45	41	58	50	45	41	56	49	44	40	54	48	44	40	39
			1.0	65	57	52	48	64	57	51	47	62	55	51	47	60	54	50	47	45
		0.56	1.25	70	63	58	54	69	62	57	54	66	61	57	53	64	60	56	53	51
下方投影面積	c m <sup>2</sup>	1.5	73	67	62	58	72	66	62	58	69	65	61	58	67	63	60	57	55	
		2.0	77	72	68	65	76	71	67	64	74	70	66	64	72	68	65	63	61	
取付高さ	器具間隔最大限		2.5	80	75	72	69	78	75	71	68	76	73	70	68	74	71	69	67	65
	横方向 (A)	縦方向 (B)	3.0	81	78	75	72	80	77	74	71	78	75	73	70	76	74	71	70	68
H m	1.25 H m	1.25 H m	4.0	83	81	78	76	82	80	77	75	80	78	76	74	78	76	75	73	71
			5.0	85	82	80	78	84	81	79	78	81	80	78	76	79	78	77	75	73
			7.0	86	84	83	81	85	83	82	81	83	82	80	79	81	80	79	78	76
			10.0	87	86	85	84	86	85	84	83	84	83	82	81	82	81	81	80	78

