

# 屋内照明器具特性

品番 (品名)	XAD3 1 2 0 L K	
光源	LLD3 0 2 0 LCB1 × 1	795.0 1 m
管理番号	K0175529 (2) DR 1	
BZ分類	BZ1	

器具効率	88 %	天井	80 %				70 %				50 %				30 %				0 %	
	上方光束		0 %	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
下方光束	88 %	床	10 %				10 %				10 %				10 %				0 %	
室指数	照明率 ( X 0.01 )																			ZCM
保守率	良	0.67	0.6	73	67	64	61	72	67	64	61	71	67	63	61	70	66	63	61	60
	中	0.63	0.8	78	73	70	68	78	73	70	67	76	72	69	67	75	71	69	67	66
	否	0.56	1.0	82	77	74	72	81	77	74	71	79	76	73	71	78	75	73	71	70
下方投影面積	等価発光面積	cm <sup>2</sup>	1.25	84	80	78	75	84	80	77	75	82	79	76	75	80	78	76	74	73
			1.5	86	83	80	78	85	82	80	78	84	81	79	77	82	80	78	76	75
取付高さ	器具間隔最大限		2.0	89	86	83	81	88	85	83	81	86	84	82	80	84	82	81	80	78
	横方向 (A)	縦方向 (B)	2.5	90	88	86	84	89	87	85	83	87	85	84	82	86	84	83	82	80
Hm	0.41Hm	0.41Hm	3.0	91	89	87	85	90	88	86	85	88	86	85	84	86	85	84	83	81
			4.0	92	90	89	88	91	90	88	87	89	88	87	86	87	86	86	85	83
			5.0	93	91	90	89	92	90	89	88	90	89	88	87	88	87	86	86	84
			7.0	93	92	92	91	92	92	91	90	90	90	89	88	89	88	88	87	85
			10.0	94	93	93	92	93	92	92	91	91	91	90	90	89	89	88	88	86

