

屋内照明器具特性

品番 (品名)	L G W 5 1 7 6 9 W				
光源	LLD4000LCB1 ×1 845.0 l m				
管理番号	K0182072 (0) DR 1				
B Z 分類	B Z 5				

器具効率	77 %	天井	80 %				70 %				50 %				30 %				0 %	
	上方光束 下方光束		12 % 65 %	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10
		床	10 %				10 %				10 %				10 %				0 %	
			室指数	照明率 (X 0 . 0 1)																Z C M
保守率	良	0.63	0.6	4.1	3.1	2.5	2.1	3.9	3.0	2.5	2.1	3.6	2.9	2.4	2.0	3.3	2.7	2.3	1.9	1.7
	中	0.6	0.8	4.8	3.9	3.3	2.8	4.6	3.8	3.2	2.8	4.3	3.6	3.1	2.7	4.0	3.4	2.9	2.6	2.3
	否	0.56	1.0	5.3	4.5	3.8	3.4	5.1	4.3	3.8	3.3	4.7	4.1	3.6	3.2	4.4	3.8	3.4	3.1	2.8
			1.25	5.8	5.0	4.4	3.9	5.5	4.8	4.3	3.9	5.1	4.5	4.1	3.7	4.8	4.3	3.9	3.6	3.2
下方投影面積			1.5	6.1	5.4	4.8	4.4	5.9	5.2	4.7	4.3	5.4	4.9	4.5	4.1	5.0	4.6	4.2	3.9	3.6
等価発光面積			2.0	6.5	5.9	5.4	5.0	6.3	5.7	5.3	4.9	5.8	5.4	5.0	4.7	5.4	5.1	4.7	4.5	4.1
取付高さ	器具間隔最大限		2.5	6.8	6.3	5.8	5.4	6.5	6.1	5.7	5.3	6.1	5.7	5.4	5.1	5.7	5.4	5.1	4.8	4.4
	横方向 (A)	縦方向 (B)	3.0	7.0	6.5	6.1	5.8	6.7	6.3	6.0	5.6	6.3	6.0	5.6	5.4	5.9	5.6	5.4	5.1	4.7
H m	1.30 H m	1.30 H m	4.0	7.2	6.9	6.5	6.2	7.0	6.7	6.3	6.1	6.5	6.3	6.0	5.8	6.1	5.9	5.7	5.5	5.0
			5.0	7.4	7.1	6.8	6.5	7.1	6.9	6.6	6.4	6.7	6.5	6.3	6.1	6.3	6.1	5.9	5.8	5.3
			7.0	7.6	7.3	7.1	6.9	7.3	7.1	6.9	6.7	6.9	6.7	6.5	6.4	6.5	6.3	6.2	6.1	5.6
			10.0	7.7	7.5	7.4	7.2	7.5	7.3	7.2	7.0	7.0	6.9	6.8	6.7	6.6	6.5	6.4	6.3	5.8

