

屋内照明器具特性	
品番 (品名)	L G W 5 1 7 6 9 B
光源	LLD4000LCB1 ×1 845.0 l m
管理番号	K0182055 (0) DR 1
B Z 分類	B Z 5

器具効率	77 %	天井	80 %				70 %				50 %				30 %				0 %		
	上方光束		11 %	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
下方光束	66 %	床	10 %				10 %				10 %				10 %				0 %		
室指数		照明率 (X 0.01)																			Z C M
保守率	良	0.63	0.6	41	31	25	21	39	30	25	21	36	29	24	20	34	27	23	19	17	
	中	0.6	0.8	48	39	33	28	46	38	32	28	43	36	31	27	40	34	29	26	23	
	否	0.56	1.0	53	45	38	34	51	43	38	33	47	41	36	32	44	38	34	31	28	
			1.25	58	50	44	39	55	48	43	39	51	45	41	37	48	43	39	36	32	
下方投影面積	c m ²		1.5	61	54	48	44	59	52	47	43	54	49	45	41	51	46	42	39	36	
	等価発光面積		c m ²	2.0	65	59	54	50	63	57	53	49	59	54	50	47	55	51	48	45	41
取付高さ	器具間隔最大限		2.5	68	63	58	54	66	61	57	53	61	57	54	51	57	54	51	49	44	
	横方向 (A)	縦方向 (B)	3.0	70	65	61	58	67	63	60	56	63	60	57	54	59	56	54	51	47	
H m	1.31 H m	1.31 H m	4.0	72	69	65	62	70	67	64	61	66	63	60	58	62	59	57	55	51	
			5.0	74	71	68	65	72	69	66	64	67	65	63	61	63	61	59	58	53	
			7.0	76	73	71	69	73	71	69	67	69	67	66	64	65	64	62	61	56	
			10.0	77	75	74	72	75	73	72	70	71	69	68	67	67	65	64	63	58	

