

屋内照明器具特性	
品番 (品名)	L G D 9 0 2 1
光源	L L D 2 4 1 1 L C B 1 × 1 5 0 0 . 0 l m
管理番号	K 0 1 9 2 0 3 4 (0) D B 1
B Z 分類	B Z 1

器具効率		83 %	反射率	天井	80 %				70 %				50 %				30 %				0 %			
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
				床	10 %				10 %				10 %				10 %				0 %			
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																			Z C M	
下方光束		83 %																						
保守率		良 中 否	0 . 6 7	0 . 6	77	74	72	70	77	73	71	70	76	73	71	70	75	73	71	70	69			
			0 . 6 3	0 . 8	80	77	75	74	80	77	75	74	79	76	75	73	78	76	74	73	73			
			0 . 5 6	1 . 0	82	80	78	76	82	79	78	76	81	79	77	76	80	78	77	76	75			
			1 . 2 5	84	82	80	78	83	81	80	78	82	80	79	78	81	80	78	77	76				
下方投影面積		c m ²	1 . 5	85	83	81	80	84	82	81	80	83	81	80	79	82	81	79	79	77				
			2 . 0	86	85	83	82	86	84	83	82	84	83	82	81	83	82	81	80	79				
取付 高さ	器具間隔最大限		2 . 5	87	86	84	83	86	85	84	83	85	84	83	82	83	83	82	81	80				
	横方向 (A)	縦方向 (B)	3 . 0	88	86	85	84	87	86	85	84	85	84	84	83	84	83	82	82	80				
H m	0 . 8 0 H m	0 . 8 0 H m	4 . 0	88	87	86	86	87	87	86	85	86	85	84	84	84	84	83	83	81				
			5 . 0	89	88	87	86	88	87	86	86	86	86	85	85	85	84	84	83	81				
			7 . 0	89	89	88	88	88	88	87	87	87	86	86	85	85	85	84	84	82				
			1 0 . 0	90	89	89	88	89	88	88	88	87	87	86	86	85	85	85	85	82				

