

屋内照明器具特性

品番 (品名)	XAD3 1 2 0 K	
光源	LLD3 0 2 0 CU1 × 1	6 1 5 . 0 l m
管理番号	K0 1 7 8 9 3 4 (0) DR 1	
B Z 分類	B Z 1	

器具効率	93 %	天井	80 %				70 %				50 %				30 %				0 %		
	上方光束 0 %		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
下方光束	93 %	床		10 %				10 %				10 %				10 %				0 %	
室指数	照明率 (X 0 . 0 1)																			Z C M	
保守率	良 0.67	0.6	0.6	77	72	68	65	77	71	68	65	75	71	68	65	74	70	67	65	64	
	中 0.63		0.8	83	78	74	71	82	77	74	71	80	76	73	71	79	76	73	71	70	
	否 0.56		1.0	86	81	78	76	85	81	78	75	84	80	77	75	82	79	77	75	74	
下方投影面積	c m ²	等価発光面積	c m ²	1.25	89	85	82	79	88	84	81	79	86	83	81	79	85	82	80	78	77
				1.5	91	87	84	82	90	87	84	82	88	85	83	81	87	84	82	81	79
取付高さ	器具間隔最大限		2.5	95	92	90	88	94	91	89	88	92	90	88	87	90	88	87	86	84	
	横方向 (A)	縦方向 (B)	3.0	96	93	92	90	95	93	91	89	93	91	90	88	91	90	88	87	85	
H m	0.34 H m	0.34 H m	4.0	97	95	94	92	96	94	93	92	94	93	91	90	92	91	90	89	87	
			5.0	98	96	95	94	97	95	94	93	95	93	93	92	93	92	91	90	88	
			7.0	98	97	96	96	97	96	96	95	95	95	94	93	93	93	92	92	89	
			10.0	99	98	98	97	98	97	97	96	96	95	95	94	94	93	93	93	90	

